



# PRAMAC GSL65D



## Product description:

Compliance with Directive 2000/14/EC on environmental noise emissions and the high level of safety, which minimizes the danger of unauthorized use or accidental damage, make this series of generators suitable for all industrial and residential applications.

DEUTZ diesel engines (prepared for BIODIESEL)

- ? Oil cooling with radiator
- ? MECCALTE electronic control alternators
- ? Galvanized casing with residential muffler
- ? Lifting hook and forklift base with trolleys
- ? Motor fluids and charged battery
- ? Oil extraction piping
- ? MCP cabinet with 4 service sockets (GSL65 optional)
- ? ETB terminal block power connection GSL65
- ? KPR Dispersed liquid collection basin (std ACP)

The images are purely indicative.

## Product features:

Phase: Three phase

Maximum power three phase (KW): 51.47

Continuous power three phase (KW): 48.76

Maximum power three phase (KVA): 64.34

Continuous power three phase (KVA): 60.95

Fuel: Diesel

Frequency (Hz): 50





Voltage (V): 400  
Emissions Regulations: Stationary Use  
Speed governor: Mechanical  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 5650  
Number cylinders: 6  
Cylinders' position: In line  
Oil capacity (L): 13.5  
Cooling: Air  
Alternator: Mecc Alte ECO/P32-2L/4, brushless  
Poles: 4  
Fuel tank capacity (L): 240  
Consumption (L/h): 10.7 at 75% of the load / 14.7 at 100% of the load  
Running time (h): 22.4 at 75% of the load / 16.3 at 100% of the load  
Length (mm): 2200  
Width (mm): 1000  
Height (mm): 1620  
Dry weight (Kg): 954  
Inverter: No  
AVR: Yes  
Compound: No  
Silenced: No  
Super silenced: No

