



# PRAMAC GSL42D AUTOMATIC

## Product description:

Using a single fluid for cooling and lubrication, LPG is one of the best choices for continuous use in harsh environmental conditions such as tropical areas.

Available in open or hooded versions, these generators are highly appreciated in the telecommunications, construction and defense sectors for their durability and reliability. All service points are accessible on one side to make maintenance quick and easy.

- ? DEUTZ diesel engines
- ? MECCALTE electronic control alternators
- ? Ready for BIODIESEL
- ? Oil cooling with radiator
- ? Industrial silencer
- ? Fork base with trolleys
- ? Motor fluids and charged battery

The images are purely indicative.

## Product features:

Phase: Three phase

Maximum power three phase (KW): 35.62

Continuous power three phase (KW): 33.85

Maximum power three phase (KVA): 44.52

Continuous power three phase (KVA): 42.31



Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 400  
Emissions Regulations: Stationary Use  
Speed governor: Mechanical  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 3110  
Number cylinders: 4  
Cylinders' position: In line  
Oil capacity (L): 10  
Cooling: Oil  
Alternator: Mecc Alte ECO/P32-3S/4, brushless  
Poles: 4  
Fuel tank capacity (L): 91  
Consumption (L/h): 8.1 at 75% of the load / 11.2 at 100% of the load  
Running time (h): 11.3 at 75% of the load / 8.1 at 100% of the load  
Length (mm): 1800  
Width (mm): 750  
Height (mm): 1518  
Dry weight (Kg): 761  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Deutz

