



PRAMAC GSL42D AUTOMATIC

Product description:

Using a single fluid for cooling and lubrication, LPG is one of the best choices for continuous use in harsh environmental conditions such as tropical areas.

Available in open or hooded versions, these generators are highly appreciated in the telecommunications, construction and defense sectors for their durability and reliability. All service points are accessible on one side to make maintenance quick and easy.

- ? DEUTZ diesel engines
- ? MECCALTE electronic control alternators
- ? Ready for BIODIESEL
- ? Oil cooling with radiator
- ? Industrial silencer
- ? Fork base with trolleys
- ? Motor fluids and charged battery

The images are purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 35.62

Continuous power three phase (KW): 33.85

Maximum power three phase (KVA): 44.52

Continuous power three phase (KVA): 42.31

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400



Emissions Regulations: Stationary Use

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 3110

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10

Cooling: Oil

Alternator: Mecc Alte ECO/P32-3S/4, brushless

Poles: 4

Fuel tank capacity (L): 91

Consumption (L/h): 8.1 at 75% of the load / 11.2 at 100% of the load

Running time (h): 11.3 at 75% of the load / 8.1 at 100% of the load

Length (mm): 1800

Width (mm): 750

Height (mm): 1518

Dry weight (Kg): 761

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Deutz