



NANNI QLS13T



Product description:

NANNI QLS13T MARINE GENERATOR 10.7KW

NANNI QLS13T is a three-phase marine generator equipped with a Kubota 4-stroke engine with Diesel power supply capable of delivering a maximum power of 10.7KW.

The NANNI QLS13T is equipped with a Kubota base engine used for years in marine and industrial applications all over the world.

Engine block in cast iron of tunnel type and distribution by gears.

The NANNI QLS13T generator is equipped with a fast-heating injector and glow plug and are located in the combustion chamber, ensuring that the engine will start even at low temperatures. The cooling system allows the engine to run at an optimal temperature. In the case of closed loop heat exchanger cooling, the coolant is cooled by seawater passing through the heat exchanger. It then cools the different components of the engine.

NANNI QLS13T is complete with freshwater and saltwater exchanger. Also available with keel cooling system, also known as Keel Cooling. Accessible seawater pump with rubber impeller.

The instrument panel allows you to start and stop the generator, and gives you important information about the generator set when it is running. Check this information regularly when the generator set is running. If your instrument panel does not match the models described in this chapter, contact your authorized Nanni Diesel dealer.

The alternator of the NANNI QLS13T provides 7 KW of power in continuous operation and can produce up to 7.9 KW. Protection level IP23 (protection level available on request).

TECHNICAL FEATURES NANNI QLS13T

Maximum three-phase power: 10.7 KW





Continuous three-phase power use: 9.5 KW

Fuel: Diesel

Voltage: 400 V

Frequency: 50 Hz

Engine: Kubota, 4-stroke

Start: Electric

Consumption: 3.3 Lt/h at full load

Length: 1081 mm

Width: 486 mm

Height: 620 mm

Weight: 264 Kg

Are you looking for a marine power generator with different technical features? Here you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Three phase

Maximum power three phase (KW): 10.7

Continuous power three phase (KW): 9.5

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: Kubota, 4 stroke

Engine rpm (rpm): 1500

Starting system: Electric

Engine capacity (cm³): 1498

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 5

Cooling: Water

Inyección : Indirect (E-TVCS)

Alternator: Leroy Somer, electronic regulator

Bore x stroke (mm): 78 x 78.4

Consumption (L/h): 3.3 at 100% of the load

Length (mm): 1081

Width (mm): 486

Height (mm): 620

Dry weight (Kg): 264

