



# NANNI QMS10M



## Product description:

### NANNI QMS10M MARINE GENERATOR 10KW

NANNI QMS10M is a three-phase marine generator equipped with a Kubota 4-stroke diesel engine capable of delivering a maximum power of 10KW.

The NANNI QMS10M is equipped with a Kubota base engine which has been used for years in marine and industrial applications all over the world.

The cooling system allows the NANNI QMS10M to operate at an optimum temperature. In the case of closed-circuit heat exchanger cooling, the coolant is cooled by seawater flowing through the heat exchanger.

The NANNI QMS10M is equipped with a closed-circuit heat exchanger.

The Kubota 4-stroke diesel engine is tested in all marine or industrial applications around the world, this engine ensures excellent performance and incredible reliability. The engine consists of cast iron tunnel type block and timing gear. The Super Glow system comes as standard equipment for cold weather starting.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS10M is improved, resulting in low fuel consumption.

NANNI QMS10M is complete with freshwater and saltwater exchanger. Also available with a keel cooling system, also known as Keel Cooling.

The NANNI QMS10M's alternator provides 8.8KW of power in continuous operation and can produce up to 10KW. Protection level IP23 (protection level available on request).



---

## TECHNICAL FEATURES NANNI QMS10M

Maximum power single-phase: 10 KW  
Single-phase continuous use power: 8.8 KW  
Fuel: Diesel  
Voltage: 230 V  
Frequency: 50 Hz  
Engine: Kubota, 4 strokes  
Starting: Electric  
Consumption: 3.3 Lt/h at full load  
Length: 1050 mm  
Width: 540mm  
Height: 710mm  
Weight: 291Kg

Are you looking for a marine power generator with different technical features? [Here](#) you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

### Product features:

Phase: Single phase  
Maximum power single phase (KW): 10  
Continuous power single phase (KW): 8.8  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Engine: Kubota, 4 stroke  
Engine rpm (rpm): 1500  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 1498  
Number cylinders: 4  
Cylinders' position: In line  
Oil capacity (L): 6.7  
Cooling: Water  
Inyección : Indirect (E-TVCS)  
Alternator: Electronic regulator  
Bore x stroke (mm): 78 x 78.4  
Consumption (L/h): 3.3 at 100% of the load  
Length (mm): 1050  
Width (mm): 540

---



Shop name

Height (mm): 710

Dry weight (Kg): 291



PrestaShop