



NANNI QMS16M SILENCED MARINE GENERATOR 16.2KW

Product price:

14,580.00 € tax excluded

Product description:

NANNI QMS16M MARINE GENERATOR 16.2KW

NANNI QMS16M is a three-phase marine generator equipped with a Kubota 4-stroke engine with Diesel power supply capable of delivering a maximum power of 16.2KW.

The NANNI QMS16M is equipped with a Kubota base engine which has been used for years in marine and industrial applications all over the world.

The NANNI QMS16M generator is equipped with a fast-heating injector and glow plug and are located in the combustion chamber, ensuring that the engine will start even at low temperatures.

The cooling system allows the NANNI QMS16M to operate at an optimal temperature. In the case of closed-loop heat exchanger cooling, the coolant is cooled by seawater flowing through the heat exchanger.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS16M is improved, resulting in low fuel consumption.

NANNI QMS16M is complete with freshwater and saltwater exchanger. Also available with a keel cooling system, also known as Keel Cooling.

The NANNI QMS16M's alternator provides 13.9 KW of power in continuous operation and can produce up to 16.2 KW. Protection level IP23 (protection level available on request).

TECHNICAL FEATURES NANNI QMS16M

Maximum power Single-phase: 16.2 KW

Continuous use power Single-phase: 13.9 KW



Fuel: Diesel Voltage: 230 V Frequency: 50 Hz

Engine: Kubota, 4-stroke

Start: Electric

Consumption: 4. 8 Lt/h at full load

Length: 1130 mm Width: 600 mm Height: 700 mm Weight: 378 Kg

Are you looking for a marine power generator with different technical features? Here you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase

Maximum power single phase (KW): 16.2 Continuous power single phase (KW): 13.9

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 230

Engine: Kubota, 4 stroke Engine rpm (rpm): 1500 Starting system: Electric Engine capacity (cm³): 2197

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 7.5

Cooling: Water

Inyección: Indirect (E-TVCS) Alternator: Electronic regulator Bore x stroke (mm): 87 x 92.4

Consumption (L/h): 4.8 at 100% of the load

Length (mm): 1130 Width (mm): 600 Height (mm): 700 Dry weight (Kg): 378

