



NANNI QMS7.5M SILENCED GENERATOR 7.5KW

Product description:

NANNI QMS7,5M MARINE GENERATOR 7.5KW

NANNI QMS7,5M is a three-phase marine generator equipped with a Kubota engine, 4 strokes with Diesel power supply capable of delivering a maximum power of 7.5KW.

The cooling system allows the NANNI QMS7,5M to work at an optimal temperature. In the case of a closed circuit heat exchanger cooling, the coolant is cooled by seawater passing through the heat exchanger. In a keel cooling system (Keel Cooling), engine heat is dissipated by passing coolant through pipes embedded in the hull.

The Kubota 4-stroke diesel engine is tested in all marine or industrial applications around the world, this engine ensures excellent performance and incredible reliability. The engine consists of cast iron tunnel type block and timing gear. The Super Glow system comes as standard equipment for cold weather starting.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS7.5M is improved, resulting in low fuel consumption.

NANNI QMS7.5M is complete with freshwater and saltwater exchanger. Also available with keel cooling system, also known as Keel Cooling. Accessible seawater pump with rubber impeller.

TECHNICAL FEATURES NANNI QMS7.5M

Maximum power Single-phase: 7.5 KW

Continuous use power Single-phase: 6.6 KW

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz



Engine: Kubota, 4-stroke
Start: Electric
Consumption: 2. 5 Lt/h at full load
Length: 950 mm
Width: 540 mm
Height: 715 mm
Weight: 271 Kg

Are you looking for a marine power generator with different technical features? Here you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase
Maximum power single phase (KW): 7.5
Continuous power single phase (KW): 6.6
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Engine: Kubota, 4 stroke
Engine rpm (rpm): 1500
Starting system: Electric
Engine capacity (cm³): 1123
Number cylinders: 3
Cylinders' position: In line
Oil capacity (L): 5.1
Cooling: Water
Inyección : Indirect (E-TVCS)
Alternator: Electronic regulator
Bore x stroke (mm): 78 x 78.4
Consumption (L/h): 2.5 at 100% of the load
Length (mm): 950
Width (mm): 540
Height (mm): 715
Dry weight (Kg): 271



