



# NANNI QMS7.5M SILENCED GENERATOR 7.5KW



## Product description:

### **NANNI QMS7,5M MARINE GENERATOR 7.5KW**

NANNI QMS7,5M is a three-phase marine generator equipped with a Kubota engine, 4 strokes with Diesel power supply capable of delivering a maximum power of 7.5KW.

The cooling system allows the NANNI QMS7,5M to work at an optimal temperature. In the case of a closed circuit heat exchanger cooling, the coolant is cooled by seawater passing through the heat exchanger. In a keel cooling system (Keel Cooling), engine heat is dissipated by passing coolant through pipes embedded in the hull.

The Kubota 4-stroke diesel engine is tested in all marine or industrial applications around the world, this engine ensures excellent performance and incredible reliability. The engine consists of cast iron tunnel type block and timing gear. The Super Glow system comes as standard equipment for cold weather starting.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS7.5M is improved, resulting in low fuel consumption.

NANNI QMS7.5M is complete with freshwater and saltwater exchanger. Also available with keel cooling system, also known as Keel Cooling. Accessible seawater pump with rubber impeller.

## TECHNICAL FEATURES NANNI QMS7.5M

Maximum power Single-phase: 7.5 KW  
Continuous use power Single-phase: 6.6 KW  
Fuel: Diesel  
Voltage: 230 V  
Frequency: 50 Hz



Engine: Kubota, 4-stroke  
Start: Electric  
Consumption: 2.5 Lt/h at full load  
Length: 950 mm  
Width: 540 mm  
Height: 715 mm  
Weight: 271 Kg

Are you looking for a marine power generator with different technical features? [Here](#) you can find the full range NANNI or other brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 7.5  
Continuous power single phase (KW): 6.6  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230  
Engine: Kubota, 4 stroke  
Engine rpm (rpm): 1500  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 1123  
Number cylinders: 3  
Cylinders' position: In line  
Oil capacity (L): 5.1  
Cooling: Water  
Inyección : Indirect (E-TVCS)  
Alternator: Electronic regulator  
Bore x stroke (mm): 78 x 78.4  
Consumption (L/h): 2.5 at 100% of the load  
Length (mm): 950  
Width (mm): 540



Height (mm): 715

Dry weight (Kg): 271

