



PRAMAC LIFTER ELECTRIC PALLET TRUCK CX12 1150x520

Product price:

2.990,40 € tax excluded

Product description:

The CX electric pallet trucks are available in different versions equipped with MOSFET technology. They are suitable for carrying loads on smooth or paved surfaces. Its small size and turning radius make it the ideal tool to work with in confined spaces, such as lorries or narrow aisles.

Manoeuvrability

Thanks to the B1 width, which is equal to the fork gauge, and the L2 measurement of 360 mm, the CX12 electronic pallet truck is the ideal tool for the handling of pallets on lorries, in supermarket aisles and any application where space is limited. This machine is the best configuration in its category thanks to the frame width, in-service weight and turning radius, thus guaranteeing great manoeuvrability and compactness.

Steering wheel and controls

- Ergonomic tiller
- Luminous indicator for battery state control.
- Butterfly valves for traction control.
- Safety pushbutton with warning buzzer.
- "Tortoise" pushbutton for slow motion, which allows for the carrying out of operations with the tiller in vertical position.

Stabilizers

Two stabilizing wheels enable movement even on more difficult surfaces thus guaranteeing maximum stability in any condition of use.

The images are purely indicative.





Product features:

Drive: Electric
Operator type: Pedestrian
Load capacity (Kg): 1200
Load centre distance (mm): 600
Load axle to end forks (mm): 886
Wheel base (mm): 1119
Service weight (Kg): 155
Axle load, laden rear (Kg): 924
Axle load, laden front (Kg): 431
Axle load, unladen front (Kg): 124
Axle load, unladen rear (Kg): 31
Tyres: front wheels: RUBBER
Tyres: stabilizers wheels: POLY.I.
Tyres: rear wheels: NYLON
Diameter steering wheels (mm): 186
Width steering wheels (mm): 50
Diameter load rollers (mm): 82
Width load rollers (mm): 82
Diameter stabilizers wheels front (mm): 75
Width stabilizers wheels front (mm): 32
Quantity rear wheels: 2
Quantity front wheels: 1 driven
Tread front (mm): 369
Tread rear (mm): 371
Lift height (mm): 115
Height of tiller in drive position max (mm): 1345
Height of tiller in drive position min (mm): 885
Height lowered (mm): 85
Overall length (mm): 1510
Length to face of forks (mm): 360
Overall width (mm): 520
Thickness fork (mm): 55
Width fork (mm): 150
Length fork (mm): 1150
Distance between fork arms (mm): 520
Ground clearance at centre of wheelbase (mm): 30
Aisle width (mm): 1782
Turning radius (mm): 1268
Travel speed laden (Km/h): 4.3
Travel speed unladen (Km/h): 4.8
Lifting speed laden (m/s): 0.03
Lifting speed unladen (m/s): 0.04
Lowering speed laden (m/s): 0.05





Lowering speed unladen (m/s): 0.02

Max gradeability laden (%): 10

Max gradeability unladen (%): 25

Service brake: Electric

Drive motor power (KW): 0.35

Lift motor power (KW): 0.4

Battery voltage (V): 24

Battery capacity min (Ah): 60

Battery capacity max (Ah): 60

Battery weight min (Kg): 25

Battery weight max (Kg): 40

Energy consumption according to VDI cycle (KWh/h): 0.28

Sound level at driver's ear: 67