



# PRAMAC LIFTER SEMI-ELECTRIC STACKER TX10/16

Product price:

**3.103,80 € tax excluded**

## Product description:

The TX Series are characterized by manual traction and electrohydraulic lifting technology. These stackers are very steady and are suitable for lifting very heavy loads safely. Version 12 (1.2 t) includes polyurethane wheels as standard to reduce resistance and effort required even with full load capacity.

### Start key and battery cut-off (isolator) switch

The start key on the TX stacker performs a double function:

- switches the stacker on/off;
- is an emergency control, i.e. it completely stops battery power supply and thus prevents the lifting of forks.

### Foot brake

The foot brake, which is available on the MX and TX machines, performs the parking brake function.

### Tiller

The plastic cover increases the ergonomic character of the handle thus rendering the raising and transport operations even "lighter".

The 3-position control lever (down, neutral, up) is positioned on the steering wheel to foster manoeuvrability.

### Adjustable buffers

The TX 12 version is equipped with adjustable buffers that minimize possible oscillation during lifting.





The images are purely indicative.

**Product features:**

Drive: Manual  
Operator type: Pedestrian  
Load capacity (Kg): 1000  
Load centre distance (mm): 600  
Load axle to end forks (mm): 630  
Wheel base (mm): 965  
Service weight (Kg): 311  
Axle load, laden rear (Kg): 1070  
Axle load, laden front (Kg): 241  
Axle load, unladen front (Kg): 210  
Axle load, unladen rear (Kg): 101  
Tyres: stabilizers wheels: RUBBER  
Tyres: rear wheels: NYLON  
Diameter load rollers (mm): 82  
Width load rollers (mm): 70  
Diameter stabilizers wheels front (mm): 200  
Width stabilizers wheels front (mm): 50  
Quantity rear wheels: 2  
Tread front (mm): 620  
Tread rear (mm): 410  
Height mast lowered (mm): 1970  
Normal free lifting (mm): 1510  
Lift height (mm): 1510  
Height mast extended (mm): 1970  
Height of tiller in drive position max (mm): 1080  
Height lowered (mm): 90  
Overall length (mm): 1750  
Length to face of forks (mm): 600  
Overall width (mm): 750  
Thickness fork (mm): 70  
Width fork (mm): 150  
Length fork (mm): 1150  
Fork carriage width (mm): 650  
Distance between fork arms (mm): 560  
Ground clearance at centre of wheelbase (mm): 20  
Aisle width (mm): 2336  
Turning radius (mm): 1440  
Lifting speed laden (m/s): 0.09  
Lifting speed unladen (m/s): 0.12





Lowering speed laden (m/s): 0.4  
Lowering speed unladen (m/s): 0.1  
Lift motor power (KW): 1.6  
Battery voltage (V): 12  
Battery capacity min (Ah): 74  
Battery capacity max (Ah): 74  
Battery weight min (Kg): 18  
Battery weight max (Kg): 18  
Sound level at driver's ear: 67  
Type of lifting: Electric