



PRAMAC LIFTER SEMI-ELECTRIC STACKER TX10/16

Product price:

3,192.00 € tax excluded

Product description:

The TX Series are characterized by manual traction and electrohydraulic lifting technology. These stackers are very steady and are suitable for lifting very heavy loads safely. Version 12 (1.2 t) includes polyurethane wheels as standard to reduce resistance and effort required even with full load capacity.

Start key and battery cut-off (isolator) switch

The start key on the TX stacker performs a double function:

- switches the stacker on/off;
- is an emergency control, i.e. it completely stops battery power supply and thus prevents the lifting of forks.

Foot brake

The foot brake, which is available on the MX and TX machines, performs the parking brake function.

Tiller

The plastic cover increases the ergonomic character of the handle thus rendering the raising and transport operations even "lighter".

The 3-position control lever (down, neutral, up) is positioned on the steering wheel to foster manoeuvrability.

Adjustable buffers

The TX 12 version is equipped with adjustable buffers that minimize possible oscillation during



lifting.

The images are purely indicative.

Product features:

Drive: Manual
Operator type: Pedestrian
Load capacity (Kg): 1000
Load centre distance (mm): 600
Load axle to end forks (mm): 630
Wheel base (mm): 965
Service weight (Kg): 311
Axle load, laden rear (Kg): 1070
Axle load, laden front (Kg): 241
Axle load, unladen front (Kg): 210
Axle load, unladen rear (Kg): 101
Tyres: stabilizers wheels: RUBBER
Tyres: rear wheels: NYLON
Diameter load rollers (mm): 82
Width load rollers (mm): 70
Diameter stabilizers wheels front (mm): 200
Width stabilizers wheels front (mm): 50
Quantity rear wheels: 2
Tread front (mm): 620
Tread rear (mm): 410
Height mast lowered (mm): 1970
Normal free lifting (mm): 1510
Lift height (mm): 1510
Height mast extended (mm): 1970
Height of tiller in drive position max (mm): 1080
Height lowered (mm): 90
Overall length (mm): 1750
Length to face of forks (mm): 600
Overall width (mm): 750
Thickness fork (mm): 70
Width fork (mm): 150
Length fork (mm): 1150
Fork carriage width (mm): 650
Distance between fork arms (mm): 560
Ground clearance at centre of wheelbase (mm): 20
Aisle width (mm): 2336
Turning radius (mm): 1440



Lifting speed laden (m/s): 0.09
Lifting speed unladen (m/s): 0.12
Lowering speed laden (m/s): 0.4
Lowering speed unladen (m/s): 0.1
Lift motor power (KW): 1.6
Battery voltage (V): 12
Battery capacity min (Ah): 74
Battery capacity max (Ah): 74
Battery weight min (Kg): 18
Battery weight max (Kg): 18
Sound level at driver's ear: 67
Type of lifting: Electric