



# PRAMAC LIFTER ELECTRIC STACKER GX12-29 BASIC

**Product price:**

**5.079,00 € tax excluded**

## **Product description:**

This compact sized stacker, powerful and reliable, is the ideal solution to work in confined spaces. The Duplex mast allows a lifting capacity from 2500 up to 3500 mm with a FreeLift version available. The reduced width (800 mm), the lateral driving system and the wide mast positioning assure great manoeuvrability, stability and visibility. The built in battery and charger with integrated cable and plug make the GX Series a plug and play unit.

The BASIC version is equipped with a starting type battery, a tiller made with metal tube and ergonomic controls. This configuration is the best value for money choice.

## **Manoeuvrability**

The overall width has the same size as the EuroPallet (800 mm) allow the unit to work in narrow spaces and corridors, increase maneuverability and reducing the turning radius.

The combination of the lateral drive, the wide mast and the low cover offer outstanding visibility.

## **Tiller BASIC**

Fully integrated ergonomic tiller system including finger tip throttle and fork controls, safety pushbutton, horn, and turtle button is the standard equipment of the GX BASIC.

## **Cover**

Strong ABS cover with storage compartments on top, easily removable to speed up maintenance operations. The bottom access opening allows an immediate disassembly of motor wheel, portal and tiller without lifting the machine. Schuko plug with spiral cable for an easy battery charging.

## **Battery pack BASIC**





The separate battery compartment is the housing of starting batteries on BASIC. Such batteries are lightweight and inexpensive and is the ideal application for the discontinuos use.

The images are purely indicative.

**Product features:**

Drive: Electric  
Operator type: Pedestrian  
Load capacity (Kg): 1200  
Load centre distance (mm): 600  
Load axle to end forks (mm): 780  
Wheel base (mm): 1234  
Service weight (Kg): 545  
Axle load, laden rear (Kg): 1187  
Axle load, laden front (Kg): 558  
Axle load, unladen front (Kg): 383  
Axle load, unladen rear (Kg): 162  
Tyres: front wheels: RUBBER  
Tyres: stabilizers wheels: POLY.C.  
Tyres: rear wheels: POLY.C.  
Diameter steering wheels (mm): 250  
Width steering wheels (mm): 76  
Diameter load rollers (mm): 82  
Width load rollers (mm): 70  
Diameter stabilizers wheels front (mm): 100  
Width stabilizers wheels front (mm): 38  
Quantity rear wheels: 2  
Quantity front wheels: 1 driven + 1  
Tread front (mm): 565  
Tread rear (mm): 410  
Height mast lowered (mm): 1987  
Lift height (mm): 2810  
Height mast extended (mm): 3392  
Height of tiller in drive position max (mm): 1310  
Height of tiller in drive position min (mm): 915  
Height lowered (mm): 90  
Overall lenght (mm): 1760  
Lenght to face of forks (mm): 609  
Overall width (mm): 800  
Thickness fork (mm): 70





Width fork (mm): 150  
Lenght fork (mm): 1150  
Fork carriage width (mm): 650  
Distance between fork arms (mm): 560  
Ground clearance at centre of wheelbase (mm): 20  
Aisle width (mm): 2210  
Turning radius (mm): 1430  
Travel speed laden (Km/h): 4.7  
Travel speed unladen (Km/h): 5.2  
Lifting speed laden (m/s): 0.11  
Lifting speed unladen (m/s): 0.19  
Lowering speed laden (m/s): 0.12  
Lowering speed unladen (m/s): 0.15  
Max gradeability laden (%): 5  
Max gradeability unladen (%): 10  
Service brake: Electric  
Drive motor power (KW): 0.7  
Lift motor power (KW): 2.2  
Battery voltage (V): 24  
Battery capacity min (Ah): 85  
Battery capacity max (Ah): 85  
Battery weight min (Kg): 34  
Battery weight max (Kg): 100  
Energy consumption according to VDI cycle (KWh/h): 0.9  
Sound level at driver's ear: 62  
Type of lifting: Electric