



# PRAMAC LIFTER ELECTRIC STACKER GX12-29 BASIC

**Product price:** 

5,079.00 € tax excluded

### **Product description:**

This compact sized stacker, powerful and reliable, is the ideal solution to work in confined spaces. The Duplex mast allows a lifting capacity from 2500 up to 3500 mm with a FreeLift version available. The reduced width (800 mm), the lateral driving system and the wide mast positioning assure great manoeuvrability, stability and visibility. The built in battery and charger with integrated cable and plug make the GX Series a plug and play unit.

The BASIC version is equipped with a starting type battery, a tiller made with metal tube and ergonomic controls. This configuration is the best value for money choice.

### Manoeuvrability

The overall width has the same size as the EuroPallet (800 mm) allow the unit to work in narrow spaces and corridors, increase maneuverability and reducing the turning radius.

The combination of the lateral drive, the wide mast and the low cover offer outstanding visibility.

#### **Tiller BASIC**

Fully integrated ergonomic tiller system including finger tip throttle and fork controls, safety pushbutton, horn, and turtle button is the standard eqiipment of the GX BASIC.

#### Cover

Strong ABS cover with storage compartments on top, easily removable to speed up maintenance



operations. The bottom access opening allows an immediate disassembly of motor wheel, portal and tiller without lifting the machine. Schuko plug with spiral cable for an easy battery charging.

## **Battery pack BASIC**

The separate battery compartment is the housing of starting batteries on BASIC. Such batteries are lightweight and inexpensive and is the ideal application for the discontinuou use.

The images are purely indicative.

#### **Product features:**

Drive: Electric

Operator type: Pedestrian Load capacity (Kg): 1200

Load centre distance (mm): 600 Load axle to end forks (mm): 780

Wheel base (mm): 1234 Service weight (Kg): 545

Axle load, laden rear (Kg): 1187 Axle load, laden front (Kg): 558 Axle load, unladen front (Kg): 383 Axle load, unladen rear (Kg): 162 Tyres: front wheels: RUBBER Tyres: stabilizers wheels: POLY.C.

Tyres: rear wheels: POLY.C.

Diameter steering wheels (mm): 250 Width steering wheels (mm): 76 Diameter load rollers (mm): 82 Width load rollers (mm): 70

Diameter stabilizers wheels front (mm): 100 Width stabilizers wheels front (mm): 38

Quantity rear wheels: 2

Quantity front wheels: 1 driven + 1

Tread front (mm): 565 Tread rear (mm): 410

Height mast lowered (mm): 1987

Lift height (mm): 2810

Height mast extended (mm): 3392

Height of tiller in drive position max (mm): 1310



Height of tiller in drive position min (mm): 915

Height lowered (mm): 90 Overall lenght (mm): 1760

Lenght to face of forks (mm): 609

Overall width (mm): 800 Thickness fork (mm): 70 Width fork (mm): 150 Lenght fork (mm): 1150

Fork carriage width (mm): 650

Distance between fork arms (mm): 560

Ground clearance at centre of wheelbase (mm): 20

Aisle width (mm): 2210
Turning radius (mm): 1430
Travel speed laden (Km/h): 4.7
Travel speed unladen (Km/h): 5.2
Lifting speed laden (m/s): 0.11
Lifting speed unladen (m/s): 0.19
Lowering speed laden (m/s): 0.12
Lowering speed unladen (m/s): 0.15

Max gradeability laden (%): 5 Max gradeability unladen (%): 10

Service brake: Electric

Drive motor power (KW): 0.7 Lift motor power (KW): 2.2 Battery voltage (V): 24

Battery capacity min (Ah): 85 Battery capacity max (Ah): 85 Battery weight min (Kg): 34 Battery weight max (Kg): 100

Energy consumption according to VDI cycle (KWh/h): 0.9

Sound level at driver's ear: 62

Type of lifting: Electric

