



MOSA GE S-8000 HBT

Product price:

1,823.35 € tax excluded

Product description:

MOSA GES-8000 HBT 6,4 KW

MOSA GES-8000 HBT is a three-phase generating set with a gasoline-powered Honda engine capable of delivering a maximum power of 6.4 KW. The MOSA GES-8000 HBT generating set is equipped with a manual recoil starter. The alternator of the MOSA GES-8000 HBT generating set is synchronous, three-phase, self-excited, self-regulated with class H insulation.

MOSA is compact and convenient to maneuver and transport thanks to its compact size, its weight of 98 kg as well as the practical tubular handles.

The MOSA GES-8000 HBT generator set with 20-liter tank has a fuel consumption of 2.4 liters/hour at 75% load for up to 8 hours autonomy.

Sockets:

1x 400V 16A 3P+N+T CEE 1x 230V 16A 2P+T CEE 1x 230V 16A 2P+T Schuko

Technical specifications MOSA GES-8000 HBT:

Three-phase output Stand-by (LTP): 8 kVA (6.4 kW) / 400V /11.5A

Three-phase output PRP: 7 kVA (5.6 kW) / 400 V / 10.1A

Single-phase output PRP 4 kW / 230 V / 17.4A

Frequency: 50 Hz

Cos ?: 0.8

ENGINE TECHNICAL DATA

Model: HONDA GX 390

Net stand-by output: 8.2 kWm (11.1 hp) Net PRP output: 6.4 kWm (8.7 hp)

Cylinders / Displacement: 1 / 389 cm³ (0.39 lt.)

Bore / Stroke: 88 / 64 (mm)



Compression ratio: 8. 2 : 1 RPM controller: Mechanical FUEL CONSUMPTION

110 % (Stand-by power): 3.5 lt./h

100 % PRP: 3.2 lt. /h 75 % PRP: 2.4 lt./h 50 % PRP: 1.6 lt./h Cooling system: Air Sump oil capacity: 1.1 lt.

ALTERNATOR CHARACTERISTICS

Continuous power: 7 kVA Standby power: 7.7 KVA

Single-phase voltage: 400 Vac

Frequency: 50 Hz

Voltage regulation accuracy: ± 4 % Sustained short-circuit current: 3 In Transient Cdt (100 % load): 15 %

Efficiency at 100 % load: 80.5 % (400V - Cos? 0.8)

Isolation: Class H

Connection - Terminals: Series - N°6

Electromagnetic Compatibility (Radio Interference Suppression): EN55011

Harmonic Distortion - THD: 4 % Direct Synchronous - Xd: 270 % Direct Transient - X'd: 20 %

Direct Subtransient - X "d: 6.5 % Quad Synchronous. - Xg: 150 %

Transitory - T'd: 33 ms
Subtransitory - T "d: 5.5 ms
Unloaded - T'do: 450ms
Short-circuit ratio Kcc: 0.60

Protection degree: IP 23 Cooling air flow: 0.062/m³/sec

Coupling - Bearings: Direct J609b - N°1

Tank capacity: 20 lt.

Run time (75% of PRP): 8.5 h

GENERAL SPECIFICATIONS

Measured acoustic power LwA (LpA pressure): 96 dB(A) (71 dB(A) @ 7m) Guaranteed acoustic power LwA (LpA pressure): 96 dB(A) (71 dB(A) @ 7m)

Performance class: G2

Length: 770 mm Width: 520 mm Height: 650 mm Weight: 98 Kg



MOSA GES-8000 HBT portable generator set - Honda gasoline engine recoil start - Three-phase alternator - Three-phase power 7 kVA (5. 6 kW)

Features:

- Recoil start
- Engine stop for low oil level
- Magnetothermal switch
- Fuel level indicator
- Protective and partially enclosed stretcher
- Silenced
- Portable
- -. Complies with EC directives for noise and safety
- AVR version on request

If you are looking for another product such as MOSA GES-8000 HBT generator set then you can browse our catalog for more <u>terrestrial generator sets</u>.

Images and technical data are not binding.

.

Product features:

Phase: Single phase / Three phase Continuous power single phase (KW): 4 Continuous power single phase (KVA): 5 Maximum power three phase (KW): 6.4 Continuous power three phase (KWA): 5.6 Maximum power three phase (KVA): 8 Continuous power three phase (KVA): 7

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+N+T CEE - 1 x 230V 16A 2P+T CEE - 1 x 230V 16A

2P+T SCHUKO

Engine: Honda GX390, 4 stroke, OHV

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000 Speed governor: Mechanical

Ignition: Recoil

Starting system: Pull starter Engine capacity (cm³): 389

Number cylinders: 1



Oil capacity (L): 1.1

Cooling: Air

Alternator: Synchronous self-excited, self-regulated

Bore x stroke (mm): 88 x 64 Fuel tank capacity (L): 20

Consumption (L/h): 2.4 at 75% of the load Running time (h): 8.3 at 75% of the load Acoustic pressure: 71 dB(A) at 7 m

Length (mm): 770 Width (mm): 520 Height (mm): 650 Dry weight (Kg): 98

Silenced: Yes

Super silenced: No ATS Switch device : No

Voltage regulator: Compound / AVR (optional)

