



PRAMAC LIFTER MANUAL STACKER MX1016

Product price:

1,603.00 € tax excluded

Product description:

MX series is not only an excellent compromise between price and performance but is also a very resistant machine. Reinforced forks, a pulley made of steel and forks driven by 4 rollers to the position set are some of the main features of the high quality of this stacker. The machine is also equipped with a foot pedal for the lifting of forks, which considerably reduces the operator's effort.

Foot brake

The foot brake, which is available on the MX and TX machines, performs the parking brake function.

Tiller

- The plastic cover increases the ergonomic character of the handle thus rendering the raising and transport operations even "lighter".
- The 3-position control lever (down, neutral, up) is positioned on the steering wheel to foster manoeuvrability.

The images are purely indicative.

Product features:

Dry weight (Kg): 210

Drive: Manual



Operator type: Pedestrian Load capacity (Kg): 1000

Load centre distance (mm): 600 Load axle to end forks (mm): 800

Wheel base (mm): 1240
Service weight (Kg): 210
Axle load, laden rear (Kg): 901
Axle load, laden front (Kg): 309
Axle load, unladen front (Kg): 129
Axle load, unladen rear (Kg): 81
Tyres: stabilizers wheels: NYLON

Tyres: rear wheels: NYLON Diameter load rollers (mm): 80 Width load rollers (mm): 70

Diameter stabilizers wheels front (mm): 150 Width stabilizers wheels front (mm): 40

Quantity rear wheels: 2 Tread front (mm): 600 Tread rear (mm): 380

Height mast lowered (mm): 2080 Normal free lifting (mm): 1510

Lift height (mm): 1510

Height mast extended (mm): 2080

Height of tiller in drive position max (mm): 1090

Height lowered (mm): 90 Overall lenght (mm): 1690

Lenght to face of forks (mm): 540

Overall width (mm): 740 Thickness fork (mm): 60 Width fork (mm): 170 Lenght fork (mm): 1150

Fork carriage width (mm): 550

Distance between fork arms (mm): 550

Ground clearance at centre of wheelbase (mm): 30

Aisle width (mm): 2166
Turning radius (mm): 1400
Lifting speed laden (m/s): 73
Lifting speed unladen (m/s): 73
Lowering speed laden (m/s): 0.12
Lowering speed unladen (m/s): 0.03

Type of lifting: Manual

