



PRAMAC LIFTER HAND PALLET TRUCK GS25S4 800x400 DOUBLE ROLLER

Product price:

571,20 € tax excluded

Product description:

GS series is a suitable practical solution meeting all the needs of manual handling. The GS PRO pallet truck is equipped as a standard with a start and exit roller and a more ergonomic handle.

Maximum pressure valve

When the maximum load capacity is exceeded, oil pressure exceeds its maximum limit and the valve automatically locks the forks. Thus possible structural damage is avoided.

Varnishing

Following an appropriate conditioning operation the frame is varnished with polyester powder at a temperature of 250° to guarantee maximum resistance to wear and atmospheric agents.

The images are purely indicative.

Product features:

Drive: Manual

Operator type: Pedestrian

Load capacity (Kg): 2500





Load centre distance (mm): 400
Load axle to end forks (mm): 582
Wheel base (mm): 842
Service weight (Kg): 54
Axle load, laden rear (Kg): 1863
Axle load, laden front (Kg): 691
Axle load, unladen front (Kg): 35
Axle load, unladen rear (Kg): 19
Tyres: front wheels: POLY.I. / NYLON
Tyres: rear wheels: NYLON
Diameter steering wheels (mm): 200
Width steering wheels (mm): 55
Diameter load rollers (mm): 82
Width load rollers (mm): 60
Quantity rear wheels: 4
Rear balancing axle: No
Tread front (mm): 155
Tread rear (mm): 250
Lift height (mm): 115
Height of tiller in drive position max (mm): 1160
Height lowered (mm): 85
Overall length (mm): 1200
Length to face of forks (mm): 400
Overall width (mm): 400
Thickness fork (mm): 55
Width fork (mm): 150
Length fork (mm): 800
Distance between fork arms (mm): 400
Ground clearance at centre of wheelbase (mm): 30
Aisle width (mm): 1435
Turning radius (mm): 1017
Lifting speed laden (strokes): 13
Lifting speed unladen (strokes): 13
Weigher: No

