



PRAMAC LIFTER HAND PALLET TRUCK GS30S4 1150x525 DOUBLE ROLLER

Product description:

Pramac Lifter GS30S4 1150x525 cm Pallet Truck

The PRAMAC Lifter GS30S4 1150x525 cm pallet truck is the entry level model to the hand pallet truck range with which it shares the characteristics of reliability and robustness.

The PRAMAC Lifter GS30S4 1150x525 cm is the practical and suitable solution for all manual handling needs and is equipped as standard with start and exit rollers with an ergonomically cut handle.

The PRAMAC Lifter GS30S4 is ideal when you don't have to handle large amounts of material every day. The PRAMAC Lifter GS30S4 pallet truck for sale in our catalog is Made in Italy.

The PRAMAC Lifter GS30S4 is built with 1150x525 cm forks and four rear wheels. This pallet truck has a capacity of 3000 kg with a lifting height of 115 mm. The stowage aisle is 1835 mm while the turning radius is 1367 mm.

When the maximum load capacity is exceeded, the oil pressure exceeds its maximum limit and the valve automatically blocks the forks. This prevents possible structural damage.

The frame, after an appropriate conditioning operation, is painted with polyester powder at a temperature of 250° to ensure maximum resistance to wear and tear and atmospheric agents.

TECHNICAL FEATURES PRAMAC Lifter GS30S4 1150x525

Propulsion Type: Manual

Driving System: Accompaniment

Load capacity: 3000 kg

Quantity of rear wheels: 4

Lifting height: 115 mm



Total length: 1550 mm

Total width: 525 mm

Fork width: 150 mm

Fork length: 1150 mm

Width between forks: 525 mm

Storage aisle: 1835 mm

Turning radius: 1367 mm

Are you looking for a pallet truck with different technical characteristics? [Here](#) you can find the area dedicated to PRAMAC pallet trucks or other specialized brands

Pictures and technical data are not binding

Product features:

Drive: Manual

Operator type: Pedestrian

Load capacity (Kg): 3000

Load centre distance (mm): 600

Load axle to end forks (mm): 932

Wheel base (mm): 1192

Service weight (Kg): 88

Axle load, laden rear (Kg): 2196

Axle load, laden front (Kg): 892

Axle load, unladen front (Kg): 59

Axle load, unladen rear (Kg): 29

Tyres: front wheels: POLY.I. / NYLON

Tyres: rear wheels: NYLON

Diameter steering wheels (mm): 200

Width steering wheels (mm): 55

Diameter load rollers (mm): 82

Width load rollers (mm): 60

Quantity rear wheels: 4

Rear balancing axle: No

Tread front (mm): 155

Tread rear (mm): 375

Lift height (mm): 115

Height of tiller in drive position max (mm): 1160

Height lowered (mm): 85

Overall lenght (mm): 1550

Lenght to face of forks (mm): 400

Overall width (mm): 525

Thickness fork (mm): 50



Width fork (mm): 150

Length fork (mm): 1150

Distance between fork arms (mm): 525

Ground clearance at centre of wheelbase (mm): 35

Aisle width (mm): 1835

Turning radius (mm): 1367

Lifting speed laden (strokes): 13

Lifting speed unladen (strokes): 13

Weigher: No

