



# PRAMAC LIFTER HAND PALLET TRUCK HX10M 1500x540

## **Product price:**

2,158.80 € tax excluded

## **Product description:**

The HX10 series, which is available in both a manual and an electric version, allows for easy and light lifting to a height of 800 mm, thus becoming a practical work platform, which is suitable for places such as machine workshops. This pallet truck is also able to carry out the support function and material supply along the assembly and production lines.

#### **Control lever**

The redesigned hydraulic unit allows for less effort at the steering wheel for all loads and a quick elevated function (30 cycles) for loads up to 150 Kg.

## **Emergency pushbutton**

The emergency pushbutton with a battery cut-off (isolator) switch function and an offload valve allows for a smoother lowering of the load; these are some of the devices that make the work safer and more efficient.

#### Front and rear stabilisers

The new control linkage makes the entry onto the closed side of the pallet possible by slight lifting, which facilitates the successive handling phases. Furthermore, more machine stability has been obtained using load rollers in a more advanced position and by providing front stabilisers as a standard. Rear stabilizers, in turn, render work stable and safe even in the case of elevated loads once the 400 mm of lifting up have been exceeded.

## Photo auto leveling system

- An automatic system which, by means of a photocell, adjusts the height of the forks, thus maintaining the work height set.
- An optical and acoustic signal is activated at every fork movement.
- Possibility of adjusting the photocell both in height and reading angle.
- Micro-switch, active both on the way up to prevent superfluous absorption of energy and on the



way down to protect the operator.

The images are purely indicative.

#### **Product features:**

**Drive: Manual** 

Operator type: Pedestrian Load capacity (Kg): 1000

Load centre distance (mm): 762 Load axle to end forks (mm): 1283

Wheel base (mm): 1531 Service weight (Kg): 200

Axle load, laden rear (Kg): 742
Axle load, laden front (Kg): 458
Axle load, unladen front (Kg): 117
Axle load, unladen rear (Kg): 83

Tyres: front wheels: POLY.I. / NYLON

Tyres: rear wheels: POLY.I.

Diameter steering wheels (mm): 200 Width steering wheels (mm): 45 Diameter load rollers (mm): 80 Width load rollers (mm): 50

Tread front (mm): 155 Tread rear (mm): 447 Lift height (mm): 715

Height of tiller in drive position max (mm): 1250

Height lowered (mm): 85 Overall lenght (mm): 1910

Lenght to face of forks (mm): 376

Overall width (mm): 540 Thickness fork (mm): 48 Width fork (mm): 160 Lenght fork (mm): 1525

Distance between fork arms (mm): 540

Ground clearance at centre of wheelbase (mm): 21

Aisle width (mm): 2275
Turning radius (mm): 1666
Lifting speed laden (m/s): 62
Lifting speed unladen (m/s): 30
Lowering speed laden (m/s): 0.06
Lowering speed unladen (m/s): 0.04

Type of lifting: Manual



