



# PRAMAC LIFTER HAND PALLET TRUCK HX10M 1150x680

**Product price:**

**1,190.00 € tax excluded**

## **Product description:**

The HX10 series, which is available in both a manual and an electric version, allows for easy and light lifting to a height of 800 mm, thus becoming a practical work platform, which is suitable for places such as machine workshops. This pallet truck is also able to carry out the support function and material supply along the assembly and production lines.

### **Control lever**

The redesigned hydraulic unit allows for less effort at the steering wheel for all loads and a quick elevated function (30 cycles) for loads up to 150 Kg.

### **Emergency pushbutton**

The emergency pushbutton with a battery cut-off (isolator) switch function and an offload valve allows for a smoother lowering of the load; these are some of the devices that make the work safer and more efficient.

### **Front and rear stabilisers**

The new control linkage makes the entry onto the closed side of the pallet possible by slight lifting, which facilitates the successive handling phases. Furthermore, more machine stability has been obtained using load rollers in a more advanced position and by providing front stabilisers as a standard. Rear stabilizers, in turn, render work stable and safe even in the case of elevated loads once the 400 mm of lifting up have been exceeded.

### **Photo auto leveling system**

- An automatic system which, by means of a photocell, adjusts the height of the forks, thus maintaining the work height set.
- An optical and acoustic signal is activated at every fork movement.
- Possibility of adjusting the photocell both in height and reading angle.
- Micro-switch, active both on the way up to prevent superfluous absorption of energy and on the



way down to protect the operator.

The images are purely indicative.

**Product features:**

Drive: Manual  
Operator type: Pedestrian  
Load capacity (Kg): 1000  
Load centre distance (mm): 600  
Load axle to end forks (mm): 993  
Wheel base (mm): 1231  
Service weight (Kg): 111  
Axle load, laden rear (Kg): 718  
Axle load, laden front (Kg): 393  
Axle load, unladen front (Kg): 76  
Axle load, unladen rear (Kg): 35  
Tyres: front wheels: POLY.I. / NYLON  
Tyres: rear wheels: POLY.I.  
Diameter steering wheels (mm): 200  
Width steering wheels (mm): 45  
Diameter load rollers (mm): 80  
Width load rollers (mm): 50  
Tread front (mm): 155  
Tread rear (mm): 587  
Lift height (mm): 715  
Height of tiller in drive position max (mm): 1250  
Height lowered (mm): 85  
Overall length (mm): 1526  
Length to face of forks (mm): 376  
Overall width (mm): 680  
Thickness fork (mm): 48  
Width fork (mm): 160  
Length fork (mm): 1150  
Distance between fork arms (mm): 680  
Ground clearance at centre of wheelbase (mm): 21  
Aisle width (mm): 2019  
Turning radius (mm): 1369  
Lifting speed laden (m/s): 62  
Lifting speed unladen (m/s): 30  
Lowering speed laden (m/s): 0.06  
Lowering speed unladen (m/s): 0.04  
Type of lifting: Manual



Shop name



PrestaShop