



PRAMAC LIFTER ELECTRIC PALLET TRUCK HX10E 2000x540

Product price:

2,950.00 € tax excluded



Product description:

The HX10 series, which is available in both a manual and an electric version, allows for easy and light lifting to a height of 800 mm, thus becoming a practical work platform, which is suitable for places such as machine workshops. This pallet truck is also able to carry out the support function and material supply along the assembly and production lines.

Control lever

The redesigned hydraulic unit allows for less effort at the steering wheel for all loads and a quick elevated function (30 cycles) for loads up to 150 Kg.

Emergency pushbutton

The emergency pushbutton with a battery cut-off (isolator) switch function and an offload valve allows for a smoother lowering of the load; these are some of the devices that make the work safer and more efficient.

Front and rear stabilisers

The new control linkage makes the entry onto the closed side of the pallet possible by slight lifting, which facilitates the successive handling phases. Furthermore, more machine stability has been obtained using load rollers in a more advanced position and by providing front stabilisers as a standard. Rear stabilizers, in turn, render work stable and safe even in the case of elevated loads once the 400 mm of lifting up have been exceeded.



Photo auto leveling system

- An automatic system which, by means of a photocell, adjusts the height of the forks, thus maintaining the work height set.
- An optical and acoustic signal is activated at every fork movement.
- Possibility of adjusting the photocell both in height and reading angle.
- Micro-switch, active both on the way up to prevent superfluous absorption of energy and on the way down to protect the operator.

The images are purely indicative.

Product features:

Drive: Manual

Operator type: Pedestrian

Load capacity (Kg): 1000

Load centre distance (mm): 1000

Load axle to end forks (mm): 1509

Wheel base (mm): 1748

Service weight (Kg): 262

Axle load, laden rear (Kg): 801

Axle load, laden front (Kg): 461

Axle load, unladen front (Kg): 169

Axle load, unladen rear (Kg): 93

Tyres: front wheels: RUBBER

Tyres: rear wheels: POLY.I.

Diameter steering wheels (mm): 200

Width steering wheels (mm): 50

Diameter load rollers (mm): 80

Width load rollers (mm): 50

Quantity rear wheels: 2

Tread front (mm): 155

Tread rear (mm): 447

Lift height (mm): 715

Height of tiller in drive position max (mm): 1300

Height lowered (mm): 85

Overall length (mm): 2543

Length to face of forks (mm): 540

Overall width (mm): 540

Thickness fork (mm): 48

Width fork (mm): 160



Lenght fork (mm): 2000
Distance between fork arms (mm): 540
Ground clearance at centre of wheelbase (mm): 21
Aisle width (mm): 2763
Turning radius (mm): 2058
Lifting speed laden (m/s): 0.08
Lifting speed unladen (m/s): 0.13
Lowering speed laden (m/s): 0.13
Lowering speed unladen (m/s): 0.06
Lift motor power (KW): 1.6
Battery voltage (V): 12
Battery capacity min (Ah): 60
Battery capacity max (Ah): 60
Battery weight min (Kg): 14
Battery weight max (Kg): 14