



PRAMAC LIFTER ELECTRIC PALLET TRUCK CX12 1000x520

Product price:

3,000.00 € tax excluded

Product description:

The CX electric pallet trucks are available in different versions equipped with MOSFET technology. They are suitable for carrying loads on smooth or paved surfaces. Its small size and turning radius make it the ideal tool to work with in confined spaces, such as lorries or narrow aisles.

Manoeuvrability

Thanks to the B1 width, which is equal to the fork gauge, and the L2 measurement of 360 mm, the CX12 electronic pallet truck is the ideal tool for the handling of pallets on lorries, in supermarket aisles and any application where space is limited. This machine is the best configuration in its category thanks to the frame width, in-service weight and turning radius, thus guaranteeing great manoeuvrability and compactness.

Steering wheel and controls

- Ergonomic tiller
- Luminous indicator for battery state control.
- Butterfly valves for traction control.
- Safety pushbutton with warning buzzer.
- "Tortoise" pushbutton for slow motion, which allows for the carrying out of operations with the tiller in vertical position.

Stabilizers

Two stabilizing wheels enable movement even on more difficult surfaces thus guaranteeing maximum stability in any condition of use.



The images are purely indicative.

Product features:

Drive: Electric

Operator type: Pedestrian Load capacity (Kg): 1200

Load centre distance (mm): 500 Load axle to end forks (mm): 736

Wheel base (mm): 969 Service weight (Kg): 153

Axle load, laden rear (Kg): 938
Axle load, laden front (Kg): 415
Axle load, unladen front (Kg): 123
Axle load, unladen rear (Kg): 30
Tyres: front wheels: RUBBER
Tyres: stabilizers wheels: POLY.I.

Tyres: rear wheels: NYLON

Diameter steering wheels (mm): 186 Width steering wheels (mm): 50 Diameter load rollers (mm): 82 Width load rollers (mm): 82

Diameter stabilizers wheels front (mm): 75 Width stabilizers wheels front (mm): 32

Quantity rear wheels: 2

Quantity front wheels: 1 driven

Tread front (mm): 369 Tread rear (mm): 371 Lift height (mm): 115

Height of tiller in drive position max (mm): 1345 Height of tiller in drive position min (mm): 885

Height lowered (mm): 85 Overall lenght (mm): 1360

Lenght to face of forks (mm): 360

Overall width (mm): 520 Thickness fork (mm): 55 Width fork (mm): 150 Lenght fork (mm): 1000

Distance between fork arms (mm): 520

Ground clearance at centre of wheelbase (mm): 30

Aisle width (mm): 1582 Turning radius (mm): 1118



Travel speed laden (Km/h): 4.3
Travel speed unladen (Km/h): 4.8
Lifting speed laden (m/s): 0.03
Lifting speed unladen (m/s): 0.04
Lowering speed laden (m/s): 0.05
Lowering speed unladen (m/s): 0.02
Max gradeability laden (%): 10

Max gradeability laden (%): 10 Max gradeability unladen (%): 25

Service brake: Electric

Drive motor power (KW): 0.35 Lift motor power (KW): 0.4 Battery voltage (V): 24

Battery capacity min (Ah): 60 Battery capacity max (Ah): 60 Battery weight min (Kg): 24 Battery weight max (Kg): 40

Energy consumption according to VDI cycle (KWh/h): 0.28

Sound level at driver's ear: 67

