



# PRAMAC LIFTER ELECTRIC PALLET TRUCK CX14 1150x525

Product price:

**4.133,50 € tax excluded**

## Product description:

The CX electric pallet trucks are available in different versions equipped with MOSFET technology. They are suitable for carrying loads on smooth or paved surfaces. Its small size and turning radius make it the ideal tool to work with in confined spaces, such as lorries or narrow aisles.

## Manoeuvrability

Thanks to the B1 width, which is equal to the fork gauge, and the L2 measurement of 360 mm, the CX12 electronic pallet truck is the ideal tool for the handling of pallets on lorries, in supermarket aisles and any application where space is limited. This machine is the best configuration in its category thanks to the frame width, in-service weight and turning radius, thus guaranteeing great manoeuvrability and compactness.

## Steering wheel and controls

- Ergonomic tiller
- Luminous indicator for battery state control.
- Butterfly valves for traction control.
- Safety pushbutton with warning buzzer.
- Forks way up/down control positioned on both sides of the handle.
- Hour counter in the Plus and Gel versions.
- "Tortoise" pushbutton for slow motion, which allows for the carrying out of operations with the tiller in vertical position.

## Stabilizers

Two stabilizing wheels enable movement even on more difficult surfaces thus guaranteeing maximum stability in any condition of use.





The images are purely indicative.

**Product features:**

Drive: Electric  
Operator type: Pedestrian  
Load capacity (Kg): 1400  
Load centre distance (mm): 600  
Load axle to end forks (mm): 935  
Wheel base (mm): 1195  
Service weight (Kg): 224  
Axle load, laden rear (Kg): 1042  
Axle load, laden front (Kg): 583  
Axle load, unladen front (Kg): 186  
Axle load, unladen rear (Kg): 38  
Tyres: front wheels: RUBBER  
Tyres: stabilizers wheels: POLY.C.  
Tyres: rear wheels: POLY.C.  
Diameter steering wheels (mm): 250  
Width steering wheels (mm): 76  
Diameter load rollers (mm): 82  
Width load rollers (mm): 80  
Diameter stabilizers wheels front (mm): 100  
Width stabilizers wheels front (mm): 40  
Quantity rear wheels: 2  
Tread front (mm): 530  
Tread rear (mm): 375  
Lift height (mm): 115  
Height of tiller in drive position max (mm): 1242  
Height lowered (mm): 85  
Overall length (mm): 1560  
Length to face of forks (mm): 411  
Overall width (mm): 720  
Thickness fork (mm): 55  
Width fork (mm): 150  
Length fork (mm): 1150  
Distance between fork arms (mm): 525  
Ground clearance at centre of wheelbase (mm): 30  
Aisle width (mm): 1810  
Turning radius (mm): 1344





Travel speed laden (Km/h): 4.3  
Travel speed unladen (Km/h): 4.8  
Lifting speed laden (m/s): 0.03  
Lifting speed unladen (m/s): 0.04  
Lowering speed laden (m/s): 0.04  
Lowering speed unladen (m/s): 0.05  
Max gradeability laden (%): 5  
Max gradeability unladen (%): 10  
Service brake: Electric  
Drive motor power (KW): 0.7  
Lift motor power (KW): 1  
Battery voltage (V): 24  
Battery capacity min (Ah): 70  
Battery capacity max (Ah): 70  
Battery weight min (Kg): 30  
Battery weight max (Kg): 30  
Sound level at driver's ear: 59 dB(A)

