



# PRAMAC LIFTER ELECTRIC PALLET TRUCK CX14 1150x525 EVO LI-ION

Product price:

**5.389,30 € tax excluded**

## Product features:

Battery type: AGM

Drive: Electric

Operator type: Pedestrian

Load capacity (Kg): 1400

Load centre distance (mm): 600

Load axle to end forks (mm): 935

Wheel base (mm): 1195

Service weight (Kg): 255

Axle load, laden rear (Kg): 1047

Axle load, laden front (Kg): 609

Axle load, unladen front (Kg): 213

Axle load, unladen rear (Kg): 42

Tyres: front wheels: RUBBER

Tyres: stabilizers wheels: POLY.C.

Tyres: rear wheels: POLY.C.

Diameter steering wheels (mm): 250

Width steering wheels (mm): 76

Diameter load rollers (mm): 82

Width load rollers (mm): 80

Diameter stabilizers wheels front (mm): 100

Width stabilizers wheels front (mm): 40

Quantity rear wheels: 2

Tread front (mm): 530

Tread rear (mm): 375

Lift height (mm): 115

Height of tiller in drive position max (mm): 1238

Height lowered (mm): 85





Overall length (mm): 1560  
Length to face of forks (mm): 411  
Overall width (mm): 720  
Thickness fork (mm): 55  
Width fork (mm): 150  
Length fork (mm): 1150  
Distance between fork arms (mm): 525  
Ground clearance at centre of wheelbase (mm): 30  
Aisle width (mm): 1810  
Turning radius (mm): 1344  
Travel speed laden (Km/h): 6  
Travel speed unladen (Km/h): 6  
Lifting speed laden (m/s): 0.03  
Lifting speed unladen (m/s): 0.04  
Lowering speed laden (m/s): 0.05  
Lowering speed unladen (m/s): 0.04  
Max gradeability laden (%): 5  
Max gradeability unladen (%): 10  
Service brake: Electric  
Drive motor power (KW): 0.7  
Lift motor power (KW): 1  
Battery voltage (V): 24  
Battery capacity min (Ah): 85  
Battery capacity max (Ah): 85  
Battery weight min (Kg): 61  
Battery weight max (Kg): 61  
Sound level at driver's ear: 59 dB(A)

