



# HONDA EM2300 Petrol Single-Phase Generator Avr

## 2.3 kW 2,87 kVA

### Product description:

#### **HONDA EM2300 SINGLE-PHASE GENERATOR AVR2.3 KW 2,87KVA**

HONDA EM2300 is a single-phase gasoline generator with 4-stroke engine capable of delivering a power of 2,87KVA 2,3KW. HONDA EM2300 represents a very interesting novelty for Individuals and Professionals who, in addition to looking for a high quality product, want a machine that guarantees high performance, maximum quality of energy delivery and great autonomy of work.

The power of 2,87KVA produced by the HONDA EM2300 is perfect for resistive loads such as drills, circular saws and concrete dowelers. The automatic voltage regulator (AVR) provides greater stability by providing a stable clean energy waveform (see image below).

The very low maintenance makes the HONDA EM2300 generator ideal for a non-stop working environment. Once in operation, it meets any requirement. And because they operate at a constant speed, the generator is always available.

HONDA EM2300 has extremely practical sockets and controls that make starting and operation of the 2,87KVA generator extremely easy and fast. Simply start it up and let it run, because the unique Oil Alert™ function will automatically turn off the unit in case of oil below the safety level.

Honda has made a motor support system with a strong steel frame. These rubber dampers, positioned on both sides of the motor and inclined at 45°, significantly reduce the vibrations of the motor of an already quiet machine. Beautiful from an aesthetic point of view, effective from a functional point of view.

#### **TECHNICAL FEATURES OF THE HONDA EM2300 HONDA GENERATOR A SINGLE-PHASE BENZINE AVR 2,3 KW 2,87KVA**

Type of Phase: Single-phase

Maximum power: 2,3KW



Continuous use power: 2 KW  
Maximum power: 2,87KVA  
Continuous use power: 2,5KVA  
Fuel: Gasoline  
Voltage: 230  
Frequency (Hz): 50Hz  
Motor: Honda GX160  
Type: 4-stroke, OHV, 1 cylinder  
Start: Manual  
Autonomy: 9h 45  
Consumption: 1.23 Lt/h  
Length: 535 mm  
Width: 435 mm  
Height: 450 mm  
Weight (Kg): 40  
Avr

Are you looking for a product with different characteristics? [HERE](#)you can find the whole range **HONDA** and other specialized brands.

Images and technical data not binding and subject to change by the manufacturer

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 2.3  
Continuous power single phase (KW): 2  
Maximum power single phase (KVA): 2.88  
Continuous power single phase (KVA): 2.5  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 2 x 230V 16A 2P+T CEE  
Engine: Honda GX160, 4 stroke, OHV  
Engine rpm (rpm): 3000  
Ignition: Transistorized  
Starting system: Manual  
Engine capacity (cm<sup>3</sup>): 163  
Number cylinders: 1  
Oil capacity (L): 0.58  
Cooling: Air



Bore x stroke (mm): 68 x 45

Fuel tank capacity (L): 12

Consumption (L/h): 1.23

Running time (h): 9.75

Acoustic power: 94 dB(A)

Acoustic pressure: 79 dB(A)

Length (mm): 535

Width (mm): 435

Height (mm): 450

Dry weight (Kg): 40

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR

Engine manufacturer: Honda

