



BM2 HOT AIR GENERATOR GP 30M

Product price:

326,25 € tax excluded

Product description:

BM2 HOT AIR GENERATOR GP 30M

BM2 GP30M is a manual start hot air generator powered by LPG, perfect for heating closed but ventilated rooms such as construction sites, greenhouses and farms.

BM2 GP30M is powered by high-pressure LPG, with an integrated, direct-burning burner. BM2 GP30M hot air generator is manufactured with manual ignition by piezoelectric. For their power supply they are usually connected to LPG cylinders, which makes them handy and very economical.

The BM2 GP30M hot air generator comes complete with:

- Built-in LPG burner
- Safety thermostat
- Control with thermocouple and gas valve
- Power supply cable with plug
- Manual ignition with piezo-electric system
- Complies with UNI EN 1596:2008

TECHNICAL FEATURES BM2 GP30M

Maximum heat output: 31.4 KW / 27000 kcal/h / 107140 BTU/h

Minimum heat output: 15.08 KW / 12965 kcal/h / 51455 BTU/h

Power supply: LPG

Maximum gas consumption: 2.014 Kg/h

Minimum gas consumption: 1.004 Kg/h

Gas pressure: 1.5 - 0.4 bar

Efficiency: 100 %

Air flow rate: 1100 m³/h



Air temperature at 20°C: 49 °C

Electrical power: 90 W

Voltage: 230 V

Phase: Single phase

Frequency: 50/60 Hz

Width: 505 mm

Length: 277 mm

Height: 511 mm

Dry weight: 10 Kg

Are you looking for a hot air generator with different technical characteristics? Here you can find the full range of hot air generators BM2 or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase

Fuel: LPG

Frequency (Hz): 50 / 60

Voltage (V): 230

Max rated heat power: 31.4 KW - 27000 Kcal/h - 107140 BTU/h

Min rated heat power: 15.08 KW - 12965 Kcal/h - 51455 BTU/h

Max Gas consumption (Kg/h): 2.014

Min Gas consumption (Kg/h): 1.004

Gas pressure (bar): 1.5÷0.4

Heat efficiency (%): 100

Air flow (m³/h): 1100

Air temperature at 20°C (°C): 49

Power consumption (W): 90

Length (mm): 505

Width (mm): 277

Height (mm): 511

Dry weight (Kg): 10

