



## PRAMAC LIFTER ELECTRIC STACKER RX10/09

## **Product price:**

4.069,00 € tax excluded

## **Product features:**

Drive: Electric

Operator type: Pedestrian Load capacity (Kg): 1000

Load centre distance (mm): 600 Load axle to end forks (mm): 786

Wheel base (mm): 1165 Service weight (Kg): 337

Axle load, laden rear (Kg): 932
Axle load, laden front (Kg): 405
Axle load, unladen front (Kg): 240
Axle load, unladen rear (Kg): 97
Tyres: front wheels: RUBBER
Tyres: stabilizers wheels: POLY.C.

Tyres: rear wheels: POLY.C.

Diameter steering wheels (mm): 186 Width steering wheels (mm): 50 Diameter load rollers (mm): 82 Width load rollers (mm): 70

Diameter stabilizers wheels front (mm): 125 Width stabilizers wheels front (mm): 45

Quantity rear wheels: 2 Tread front (mm): 505 Tread rear (mm): 410

Height mast lowered (mm): 1270 Normal free lifting (mm): 810

Lift height (mm): 810

Height mast extended (mm): 1270

Height of tiller in drive position max (mm): 1365 Height of tiller in drive position min (mm): 930





Height lowered (mm): 90 Overall lenght (mm): 1675

Lenght to face of forks (mm): 522

Overall width (mm): 794
Thickness fork (mm): 60
Width fork (mm): 150
Lenght fork (mm): 1153

Fork carriage width (mm): 650

Distance between fork arms (mm): 560

Ground clearance at centre of wheelbase (mm): 20

Aisle width (mm): 2120
Turning radius (mm): 1344
Travel speed laden (Km/h): 3.7
Travel speed unladen (Km/h): 4.3
Lifting speed laden (m/s): 0.11
Lifting speed unladen (m/s): 0.18
Lowering speed laden (m/s): 0.18

Max gradeability laden (%): 9 Max gradeability unladen (%): 25

Service brake: Electric

Drive motor power (KW): 0.35 Lift motor power (KW): 2.2

Battery voltage (V): 24

Battery capacity min (Ah): 70 Battery capacity max (Ah): 70 Battery weight min (Kg): 32 Battery weight max (Kg): 32

Energy consumption according to VDI cycle (KWh/h): 0.45

Sound level at driver's ear: 63

Type of lifting: Electric

