



SINCRO FK2 MFS Single Phase Synchronous AC Alternator 12 kVA Capacitor

Product description:

SINCRO FK2 MFS ALTERNATOR 14,4 KVA SINGLE-PHASE

Alternator SINCRO FK2 MFS Singlephase with a power of 14,4KVA, this unit has a Brushless operation equipped with capacitor voltage regulator.

The alternator is foreseen to work at frequency 50 or 60 HZ, the possibility to work on these two frequencies makes possible its application for any service voltage increasing its versatility, for a correct operation.

All the components that make up the SINCRO FK2 MFS alternator are subjected to a specific coating and/or impregnation process aimed at safeguarding the functionality of the generator and protecting the critical peers in the various conditions of use.

For extreme weather conditions, models are available that also guarantee IP23 standard protection against water up to 60° from vertical. SINCRO FK2 MFS is a brushless alternator, this feature together with the high efficiency of the regulator ensure a low level of interference with radio waves.

SINCRO alternators are all equipped with a voltage regulator, in the case of the FK2 MFS model with capacitor.

Select the alternator that reflects the **technical specifications you require**, visit our dedicated section to find out how.

TECHNICAL FEATURES SINCRO FK2 MFS

Phase Type: Single-phase

Maximum singlephase output: 11.52 KW





Maximum singlephase continuous output: 9.6 KW

Maximum singlephase output: 14.4 KVA

Maximum singlephase continuous output: 12.0 KVA

Frequency: 50-60 Hz

Voltage: 230 V

Protection rating: IP23 Agent speed: 3000 rpm Number of poles: 2

Weight: 58Kg Brushless

Voltage regulator: Condenser

Looking for a product with different features? Here you can find the full range SINCRO and other specialized brands.

Images and technical data not binding and subject to change by the manufacturer

Product features:

Phase: Single phase Frequency (Hz): 50 Voltage (V): 230

Engine rpm (rpm): 3000

Poles: 2

Single-phase power (KW): 12 Single-phase power (KVA): 12

Efficiency (%): 81.2 Protection degree: IP23 Dry weight (Kg): 58

Brushes: No

Type of alternator: Constant Speed

Voltage regulator: Capacitor

