



CGM 40TR PTO GENERATOR SINGLE- PHASE / THREE-PHASE 40 KVA AVR

Product price:

3,427.50 € tax excluded

Product description:

CGM 40TR PTO GENERATOR SINGLE-PHASE / THREE-PHASE 40 KVA AVR

CGM 40TR single/three-phase PTO generator with 3000 rpm tractor attachment, delivers a power of 40KVA and is complete with AVR voltage regulator.

The CGM 40TR is easy to transport, install and position thanks to its compact size, this model is ideal to be mounted on a tractor unit. The CGM 40TR has a required tractor power of 75 HP and a PTO speed of 435 rpm.

These compact, robust and easy-to-use generators are complete with base with 3-point hitch for secure attachment to any tractor. The motion is transmitted via the cardan joint (not included), connected to the generator set multiplier.

The CGM 40TR for attachment to the tractor are mainly designed for farms, farms, livestock and mountain pastures but easily adapt to any emergency situation.

The voltage regulator, applied to synchronous current genset, has the aim of maintaining constant operation of the machine, in its highest efficiency regime . Generally, this means keeping the power factor at values ??close to 1, but if the synchronous machine is also used to power factor correction other users present in the same installation, these values ??may vary.

Technical characteristics CGM 40TR:

Phase type: Singlephase / Threephase

Continuous output: 40 KVA / 32 KW

Emergency output: 44 KVA / 35.2 KW

Voltage: 230/400 V



Frequency : 50 Hz

Engine rpm: 3000 rpm

Necessary tractor power: 75 hp

PTO speed: 435 rpm

Multiplier ratio: 1: 6.9

Oil multiplier capacity: 0.5 Lt

Alternator: Zanardi, self-excited, with brushes

Voltage regulator: AVR

Length: 950 mm

Width: 850 mm

Height: 800 mm

Weight: 233 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the entire range of CGM cardan generator sets or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Product features:

Phase: Single phase / Three phase

Maximum power three phase (KW): 35.2

Continuous power three phase (KW): 32

Maximum power three phase (KVA): 44

Continuous power three phase (KVA): 40

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration:

Engine rpm (rpm): 3000

Oil capacity (L): 0.5

Alternator: With brushes

Poles: 2

Protection degree: IP21

PTO speed (round/min): 440

Required tractor power: 75 HP

Transmission ratio: 1 : 6.9

Length (mm): 950

Width (mm): 950

Height (mm): 900

Dry weight (Kg): 233

Silenced: No



Super silenced: No

Voltage regulator: AVR

