



# CGM 220SBE -MOTOSALDATRICE A STRAPPO

**Product price:** 

1,870.00 € tax excluded

## **Product description:**

## CGM 220SBE - SINGLEPHASE MOTORWELDING WITH WELDING POINT

CGM 220SBE is a light and versatile singlephase motorwelder equipped with a Honda GX270 petrol engine capable of delivering a maximum output of 4KVA.

The CGM 220SBE motorwelder is equipped with Honda gasoline engines with recoil start. Mounted on a fixed base and operating at 3000 rpm, they are suitable for welding and three-phase 400V power supply.

### TECHNICAL FEATURES CGM 220SBE

Phase type: Singlephase

Maximum singlephase output: 3.2 KW / 4 KVA

Engine: Honda GX390

Fuel: Gasoline Cylinders: 1

Displacement: 389 cm3 Max motor power: 13 HP

Max welding current : 200-170 A at 35%/60%

Tank: 6.5 Lt

Socket: N.2 x 230V SCHUKO Boosting: Electric with battery Acoustic Power: 70 dB(A) at 7 m

Voltage: 230 V Frequency: 50 Hz



Power Factor: 0.8

Welding current: 50-200 A Number of turns: 3000 rpm

Cooling : Air Autonomy : 3.3 h

Consumption at 3/4 load: 2 L/h

Oil capacity: 1.1 Lt

Alternator: SINCRO, with brushes

Number of Poles : 2 Number of Phases : 1 Welding voltage : 22 - 28 V

Output consumption: 11.5 hp/8.5 KW

Voltage regulation: Condenser

Width: 740 mm Length: 450 mm Height: 500 mm Weight: 98 Kg

Are you looking for a motorwelding with different technical characteristics? <u>Here</u> you can find the full range of CGM or other specialized brands

Images and technical data are not binding and may be subject to revision by the supplier.

### **Product features:**

Phase: Single phase

Maximum power single phase (KW): 3.2 Maximum power single phase (KVA): 4

Fuel: Gasoline Frequency (Hz): 50 Voltage (V): 230

Sockets configuration: 2 x 230V SCHUKO

Engine: Honda GX390 Engine rpm (rpm): 3000 Starting system: Electric Engine capacity (cm³): 389

Number cylinders: 1 Oil capacity (L): 1

Cooling: Air

Alternator: With brushes

Poles: 2

Welding current (A): 200 at 35% / 170 at 60%

Welding voltage min/max (V): 22 / 28 V



Fuel tank capacity (L): 6.5

Consumption (L/h): 2 at 75% of the load

Running time (h): 3.3

Acoustic pressure: 70 dB(A) at 7 m

Length (mm): 450 Width (mm): 740 Height (mm): 500 Dry weight (Kg): 98

Silenced: Yes

Super silenced: No

