



Shop name



# CGM 10P - COFANATO CON CENTRALINA AUTOMATICA

Product price:

**7,440.00 € tax excluded**

## Product description:

**CGM 10P-C20 Single/three-phase 11KVA super-silenced generator with automatic control panel**

The CGM 10P-C20 is a single/three phase 11KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. The CGM 10P-C20 is equipped with a weatherproof, structural steel sheet soundproof cabin and an interior cladding of high noise reduction material, making the CGM 10P-C20 supersilenced.

The CGM 10P-C20 generator consists of a Linz, Stamford or Mecc Alte, self-excited, brushless alternator with AVR voltage regulator. The CGM 10P-C20 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 2 litres per hour at 75% load. In addition, it is equipped with a panel with an automatic control unit and terminal block for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites. The CGM 10P-C20 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

## Technical characteristics of the CGM 10P-C20 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 8.8 KW / 11 KVA

Three-phase continuous power: 8 KW / 10 KVA

Maximum single-phase power: 2.9 KW / 3.67 KVA

Single-phase continuous use power: 2.67 KW / 3.3 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 403A-11G

Engine speed: 1500 rpm

Starting: Electric



Consumption: 2 Lt/h at 75% load  
Length: 1580 mm  
Width: 700 mm  
Height: 1050 mm  
Weight: 440 Kg  
Supersilenced  
AVR

If you are looking for a product like the CGM 10P-C20 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 2.9  
Continuous power single phase (KW): 2.67  
Maximum power single phase (KVA): 3.67  
Continuous power single phase (KVA): 3.3  
Maximum power three phase (KW): 8.8  
Continuous power three phase (KW): 8  
Maximum power three phase (KVA): 11  
Continuous power three phase (KVA): 10  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: Morsettiera  
Engine: PERKINS 403A-11G  
Emissions Regulations: Stationary Use  
Engine rpm (rpm): 1500  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 1131  
Number cylinders: 3  
Cooling: Water  
Alternator: Brushless  
Poles: 4  
Protection degree: IP44  
Bore x stroke (mm): 77 x 81  
Fuel tank capacity (L): 55  
Consumption (L/h): 2  
Running time (h): 27.5

---



---

Acoustic pressure: 68 dB(A) at 7 m  
Length (mm): 1580  
Width (mm): 700  
Height (mm): 1050  
Dry weight (Kg): 440  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Perkins