



# TELWIN THUNDER 304 CE HONDA

## Product description:

TELWIN THUNDER 304CE MOTORWELDING MACHINE 15,5KW

TELWIN THUNDER 304CE is a motorwelder equipped with a HONDA GX630 engine powered by gasoline, providing a threephase output of 15,5kW.

TELWIN THUNDER 304CE is a gasoline-powered motorwelder (HONDA engine) for MMA electrode welding in DC.

Flexibility of use with the most varied types of electrodes: rutile, basic, cellulosic, stainless steel, aluminum, cast iron, etc.

TELWIN THUNDER 304CE Can be used as a single-phase and three-phase generator to all types of power tools (e.g. grinders, drills, dowels, breakers, etc.), compressors, neon and incandescent lighting systems, etc.

## Features:

- Air-cooled 4-stroke twin-cylinder gasoline engine
- Electric start with ignition key
- Three ranges of welding current adjustment
- Three-phase 10.0 KVA socket and single-phase 4.0 KVA socket with protection
- Thermostatic protection
- Automatic low oil pressure lock
- Fuel tank with level indicator.

## TECHNICAL FEATURES TELWIN THUNDER 304CE

PhaseType: SinglePhase - ThreePhase

Frequency: 50 Hz

Voltage: 400 V

Welding Current Type: DC





Welding Type: MMA  
No-load Voltage: 85 V  
Current setting: 40 - 300 A  
Max DC current (EN 60974-1): 300 @ 35 % A  
Power: 15.5kW  
Mechanical power: 20.8Hp  
DC current: 250 A  
Electrode diameter: 1.6 - 6 mm  
Fuel: Gasoline  
Engine: HONDA GX630  
Starting: Electric  
RPM: 3000 rpm  
Protection Class: IP23  
Displacement: 688 cm<sup>3</sup>  
Servoir Capacity: 18 l  
Acoustic Power: 78 @ 7m dB  
Length: 940 mm  
Width: 570 mm  
Height: 790 mm  
Weight: 163 Kg

Are you looking for a welding machine with different technical characteristics? Here you can find the whole range TELWIN or other specialized brands.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase / Three phase  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: Honda GX630, 4 stroke  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 688  
Cooling: Air  
Single-phase power (KVA): 4  
Three-phase power (KVA): 10  
Protection degree: IP23  
No-load voltage (V): 85  
Regulation current (A): 40 - 300  
Diameter electrodes (mm): 1.6 - 6  
Type of welding current: DC



Type of welding: MMA  
Current max (A): 300  
Fuel tank capacity (L): 18  
Acoustic pressure: 78 dB(A) at 7 m  
Length (mm): 940  
Width (mm): 570  
Height (mm): 790  
Weight (Kg): 163