



Shop name



TELWIN THUNDER 304 CE HONDA

Product price:

4,230.00 € tax excluded

Product description:

TELWIN THUNDER 304CE MOTORWELDING MACHINE 15,5KW

TELWIN THUNDER 304CE is a motorwelder equipped with a HONDA GX630 engine powered by gasoline, providing a threephase output of 15,5kW.

TELWIN THUNDER 304CE is a gasoline-powered motorwelder (HONDA engine) for MMA electrode welding in DC.

Flexibility of use with the most varied types of electrodes: rutile, basic, cellulosic, stainless steel, aluminum, cast iron, etc.

TELWIN THUNDER 304CE Can be used as a single-phase and three-phase generator to all types of power tools (e.g. grinders, drills, dowels, breakers, etc.), compressors, neon and incandescent lighting systems, etc.

Features:

- Air-cooled 4-stroke twin-cylinder gasoline engine
- Electric start with ignition key
- Three ranges of welding current adjustment
- Three-phase 10.0 KVA socket and single-phase 4.0 KVA socket with protection
- Thermostatic protection
- Automatic low oil pressure lock
- Fuel tank with level indicator.

TECHNICAL FEATURES TELWIN THUNDER 304CE

PhaseType: SinglePhase - ThreePhase



Frequency: 50 Hz
Voltage: 400 V
Welding Current Type: DC
Welding Type: MMA
No-load Voltage: 85 V
Current setting: 40 - 300 A
Max DC current (EN 60974-1): 300 @ 35 % A
Power: 15.5kW
Mechanical power: 20.8Hp
DC current: 250 A
Electrode diameter: 1.6 - 6 mm
Fuel: Gasoline
Engine: HONDA GX630
Starting: Electric
RPM: 3000 rpm
Protection Class: IP23
Displacement: 688 cm³
Servoir Capacity: 18 l
Acoustic Power: 78 @ 7m dB
Length: 940 mm
Width: 570 mm
Height: 790 mm
Weight: 163 Kg

Are you looking for a welding machine with different technical characteristics? [Here](#) you can find the whole range TELWIN or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: Honda GX630, 4 stroke
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 688
Cooling: Air
Single-phase power (KVA): 4
Three-phase power (KVA): 10
Protection degree: IP23
No-load voltage (V): 85



Regulation current (A): 40 - 300
Diameter electrodes (mm): 1.6 - 6
Type of welding current: DC
Type of welding: MMA
Current max (A): 300
Fuel tank capacity (L): 18
Acoustic pressure: 78 dB(A) at 7 m
Length (mm): 940
Width (mm): 570
Height (mm): 790
Weight (Kg): 163