



TELWIN MASTERMIG 400 230-400V

Product description:

MIG-MAG/FLUX/BRAZING welding machine with removable wire feeder, fit for use in the industrial field.

Flexibility of use with a wide range of materials such as steel, stainless steel, high strength steels and aluminium.

Features:

- Very strong
- Numerous steps for regulation of arc voltage
- Regulation of spot welding time
- Two positions for reactance
- Thermostatic protection

Thanks to the extensions (optional) it is possible to increase the working range between wire feeder and power source up to 10 meters.

Complete with MIG-MAG welding accessories.

Not binding images and technical data.

Product features:

Phase: Single phase / Three phase

Frequency (Hz): 50 / 60

Voltage (V): 230 / 400

Protection degree: IP22

No-load voltage (V): 45.5

Adjustment positions: 18

Regulation current (A): 50 - 400



Ø steel welding wire (mm): 0.6 - 1.6

Ø inox welding wire (mm): 0.8 - 1.6

Ø aluminium welding wire (mm): 0.8 - 1.2

Ø flux cored welding wire (mm): 1 - 1.2

Ø brazing wire (mm): 0.8 - 1.2

Type of welding: MIG-MAG

MIG-MAG welding: MIG-MAG/FLUX/BRAZING

Current max (A): 400

Length (mm): 945

Width (mm): 565

Height (mm): 830

Weight (Kg): 104