



TELWIN TECHNOMIG 180 DUAL SYNERGIC EURO 230V

Product price:

507,00 € tax excluded

Product description:

Microprocessor controlled MIG-MAG/FLUX/BRAZING inverter wire welding machine.

Technomig is confirmed as the perfect solution for a wide range of applications, from maintenance to installation and interventions in body shops, because of its flexibility and the different materials it can weld (steel, stainless steel, aluminium), or braze weld (galvanized sheet).

The fast SYNERGIC adjustment of the welding parameters thanks to the "ONE TOUCH" technology, makes the product very easy to use.

Just set the material thickness and start welding: the intelligent and automatic control of the arc, moment by moment, maintains high welding performance in all working conditions, with different materials and/or gases.

The operator can also intervene manually along the arc length: this adjustment means the weld seam can be modified according to the welder's style.

Lightweight and very compact, Technomig can be moved around easily in all intervention areas, both indoors and outdoors.

Characteristics:

- Polarity change for GAS MIG-MAG/BRAZING welding
- Synergic adjustment with setting only of the material thickness
- Fine adjustment of the arc length
- 10 synergy curves available
- Compact and light
- Thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections

Fit for NO GAS/Flux welding, it can be transformed into MIG-MAG with the optional kit.

Complete with MIG-MAG torch, work clamp and cable.

Not binding images and technical data.



Product features:

Phase: Single phase

Frequency (Hz): 50 / 60

Voltage (V): 230

Efficiency (%): 86

Protection degree: IP23

No-load voltage (V): 60

Regulation current (A): 20 - 170

Ø steel welding wire (mm): 0.6 - 0.8

Ø inox welding wire (mm): 0.8

Ø aluminium welding wire (mm): 0.8 - 1

Ø flux cored welding wire (mm): 0.8 - 1.2

Ø brazing wire (mm): 0.8

Type of welding: MIG-MAG

MIG-MAG welding: MIG-MAG/FLUX/BRAZING

Current max (A): 140

Length (mm): 460

Width (mm): 240

Height (mm): 360

Voltage regulator: Inverter

Weight (Kg): 12.1

