



TELWIN ELECTROMIG 300 SYNERGIC 400V

Product price:

1,641.00 € tax excluded

Product description:

MIG-MAG/FLUX/BRAZING/MMA and TIG DC-Lift multiprocess inverter welding machine controlled by a microprocessor, with 4-roller wire feeder.

Flexible use with various welded materials (steel, stainless steel, aluminium) or brazed materials (galvanised sheet metal). Wide variety of application fields, from industry to maintenance, installation to bodywork activities.

Synergic adjustment makes the product simple to use.

The Made in Telwin ATC technology makes it easy to achieve excellent standards of welding on thin materials thanks to state-of-the-art control of the arc.

Features:

- Manual or synergic operating;
- 30 pre-set synergic curves;
- MIG-MAG adjustments: wire up slope, electronic reactance, wire burn-back time, post gas;
- 2/4 time operation selection, spot, inch and mm material thicknesses;
- Protections: thermostatic, overvoltage, undervoltage, overcurrent, engine driven generator (+/-15%);
- TIG Lift

Complete with MIG-MAG torch, cable and earth clamp.

Not binding images and technical data.

Product features:

Phase: Three phase Frequency (Hz): 50 / 60



Voltage (V): 400 Efficiency (%): 90

Protection degree: IP23 No-load voltage (V): 63

Regulation current (A): 20 - 300 Diameter electrodes (mm): 1.6 - 6 Ø steel welding wire (mm): 0.6 - 1.2 Ø inox welding wire (mm): 0.8 - 1.2

Ø aluminium welding wire (mm): 0.8 - 1.2 Ø flux cored welding wire (mm): 0.8 - 1.2

Ø brazing wire (mm): 0.8 - 1.2 Type of welding: Multiprocess

MIG-MAG welding: MIG-MAG/FLUX/BRAZING

Current max (A): 270 Length (mm): 865 Width (mm): 390 Height (mm): 915

Voltage regulator: Inverter

Weight (Kg): 37