



KOHLER 13.5 EFKOZD Three-phase Marine Genset 16.9 kVA

Product description:

Kohler 13,5EFKOZD three-phase super-silenced 16.9 KVA AVR marine generator

Marine generator Kohler 13,5EFKOZD three-phase 16,9 KVA with 1500 rpm motor. The KOHLER 13,5EFKOZD three-phase marine generator is built with a soundproof enclosure that makes it **supersilenced**. The KOHLER 13,5EFKOZD three-phase marine generator is built with a 3-cylinder, 4-cycle, diesel-powered Kohler engine, closed cooling system with heat exchanger. The alternator of the KOHLER 13,5EFKOZD three-phase marine generator is brushless, with **AVR** voltage regulator and water-cooled. The 13,5EFKOZD marine generator is compact and small in size, so it is perfect for installation on boats of various sizes.

Technical data:

Phase type: Three-phase

Three-phase continuous power: 13.5 KW

Three-phase continuous power: 16. 9 KVA

Fuel: Diesel

Frequency: 50 Hz

Voltage: 110/190 V, 115/230 V, 120/208 V, 230/400 V, 240/416 V, 220/380 V

Motor: Kohler

Motor RPM: 1500 rpm

Length: 1064 mm

Width: 652.5 mm

Height: 711 mm

Dry weight: 393 Kg

Features of the KOHLER 13,5EFKOZD marine generator

- Class H insulation
- Multi-voltage adjustability
- Voltage adjustment of 1.0%.



- Radio suppression

Engine features of the KOHLER 13,5EFKOZD marine generator

- Diesel
- Environmental Protection Agency (EPA) certified for compliance with Tier III marine auxiliary standards (60 Hz model only)
- Three cylinders
- Four cycles
- Closed cooling system
- Heat exchanger
- Electric fuel lift pump
- Lifting eyelet
- Low oil pressure shutdown
- High temperature engine shutdown
- Low seawater pressure shutdown
- Vibromount
- Belt guard
- Disposable oil filter
- Oil drain valve
- Disposable fuel filter

Features of the KOHLER 13,5EFKOZD marine generator alternator

- Brushless rotating field design allows power to be obtained from stationary conductors.
- Windings are vacuum-impregnated with epoxy paint for reliability and long life.
- Rotors are dynamically balanced to minimize vibration.
- Copper windings ensure minimal heat buildup. Insulation meets NEMA standards for Class H insulation.
- Connected directly to the motor, the generator features sealed precision ball bearings with a precision machined steel sleeve in the end bracket to prevent shaft misalignment and extend bearing life.
- Mounted on a drip-proof tray.
- Equipped with a twelve-conductor reconnectable stator.
- Capable of withstanding a line-to-neutral short-circuit current of up to 300% of rated current for up to 2 seconds. (Short circuit performance IEC 60092-301).

On our catalog of [marine generators](#) you can find other marine generators such as the KOHLER 13,5EFKOZD .

Images and technical data are not binding.



Product features:

Phase: Three phase
Continuous power three phase (KW): 13.5
Continuous power three phase (KVA): 17
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230
Engine: Kohler
Engine rpm (rpm): 1500
Speed governor: Mechanical
Engine capacity (cm³): 1900
Number cylinders: 3
Cooling: Water
Bore x stroke (mm): 88 x 102
Compression ratio: 17 : 1
Motor insulation class: H
Consumption (L/h): 2.9 at 75% of the load
Length (mm): 1064
Width (mm): 652.5
Height (mm): 711
Dry weight (Kg): 393
Silenced: Yes
Super silenced: Yes
Type of combustion: Direct
Product type: Generator
Voltage regulator: AVR
Engine manufacturer: Kohler