



# MARINE GENERATOR SET KOHLER 21 EKOZD Three-phase 26.3 kVA 60 Hz

## Product description:

### Super-silenced three-phase KOHLER 21EKOZD marine generator 26,3 KVA AVR

KOHLER 21EKOZD three-phase 26,3KVA marine generator with 1500 rpm motor. The KOHLER 21EKOZD three-phase marine generator is built with a soundproof enclosure that makes it supersilenced. The KOHLER 21EKOZD three-phase marine generator is built with a 4-cylinder, 4-cycle Kohler diesel-powered engine, closed cooling system with heat exchanger. The alternator of the three-phase KOHLER 21EKOZD is brushless with AVR voltage regulator and water-cooled. The AVR voltage regulator protects your connected sensitive devices from voltage surges. Due to its compactness and small size, the 21EKOZD is also suitable on boats of various sizes.

## Main Features:

Phase Type: Three-phase

Three-phase Continuous Power: 21 KW

Three-phase Continuous Power: 26. 3 KVA

Fuel: Diesel

Frequency: 60 Hz

Voltage: 120/208 V, 120/240 V, 127/220 V, 139/240 V, 277/480 V

Motor: Kohler

Motor speed: 1800 rpm

Length: 1197 mm

Width: 652.5 mm

Height: 711 mm

Dry weight: 462 Kg

#### Features of the KOHLER 21EKOZD

- Class H insulation



- Multi-voltage adjustability
- Voltage adjustment of 1.0%.
- Radio suppression

**Engine features of the KOHLER 21EKOZD**

- Diesel
- Environmental Protection Agency (EPA) certified for compliance with Tier III marine auxiliary standards (60 Hz model only)
- Four cylinders
- Four cycles
- Closed cooling system
- Heat exchanger
- Electric fuel lift pump
- Lifting eyelet
- Low oil pressure shutdown
- High temperature engine shutdown
- Low seawater pressure shutdown
- Vibromount
- Belt guard
- Disposable oil filter
- Oil drain valve
- Disposable fuel filter

**Features of the KOHLER 21EKOZD**

- Brushless rotating field design allows power to be obtained from stationary conductors.
- Windings are vacuum-impregnated with epoxy paint for reliability and long life.
- Rotors are dynamically balanced to minimize vibration.
- Copper windings ensure minimal heat buildup. Insulation meets NEMA standards for Class H insulation.
- Connected directly to the motor, the generator features sealed precision ball bearings with a precision machined steel sleeve in the end bracket to prevent shaft misalignment and extend bearing life.
- Mounted on a drip-proof tray.
- Equipped with a twelve-conductor reconnectable stator.
- Capable of withstanding a line-to-neutral short-circuit current of up to 300% of rated current for up to 2 seconds. (Short circuit performance IEC 60092-301).

Other marine generators such as the KOHLER 21EKOZD can be found by browsing the entire catalog of [marine generators](#).

Images and technical data are not binding.



### Product features:

Phase: Three phase

Continuous power three phase (KW): 21

Continuous power three phase (KVA): 26.3

Fuel: Diesel

Frequency (Hz): 60

Engine: Kohler

Engine rpm (rpm): 1800

Speed governor: Mechanical

Engine capacity (cm<sup>3</sup>): 2500

Number cylinders: 4

Cooling: Water

Bore x stroke (mm): 88 x 102

Compression ratio: 17 : 1

Motor insulation class: H

Consumption (L/h): 5.26 at 75% of the load

Length (mm): 1197

Width (mm): 652.5

Height (mm): 711

Dry weight (Kg): 462

Silenced: Yes

Super silenced: Yes

Type of combustion: Direct

Product type: Generator

Voltage regulator: AVR

Engine manufacturer: Kohler

