

## GREEN POWER GP88A-P-N OPEN

Product price:

11.635,00 € tax excluded

## **Product description:**

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cuttingedge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

## You can choose between the versions:

-Open group with AVR-Leroy alternator (automatic power pack)

-Open group with AVR-Mecc Alte alternator (automatic power pack)

-Open group with AVR-Stamford alternator (automatic power pack)

The image is purely indicative.

## Product features:

Phase: Three phase Maximum power three phase (KW): 4.6 Continuous power three phase (KW): 64 Maximum power three phase (KVA): 5.7

PrestaShop

R



Continuous power three phase (KVA): 80 Fuel: Diesel Frequency (Hz): 50 Voltage (V): 230 / 400 Engine: PERKINS 1104A-44TG2, 4 stroke turbo-aftercooler **Emissions Regulations: NON EMISSIONATO** Engine rpm (rpm): 1500 Speed governor: Mechanical Starting system: Elettrico Engine capacity (cm<sup>3</sup>): 686 Number cylinders: 4 Cylinders' position: In line Cooling: Water Alternator: MECC ALTE ECP32-2L/4 Poles: 4 Protection degree: IP32 Fuel tank capacity (L): 100 Consumption (L/h): 4 al 75% del carico Running time (h): 9.62 h al 75% del carico Length (mm): 2100 Width (mm): 900 Height (mm): 1300 Dry weight (Kg): 940 Silenced: No Super silenced: No ATS Switch device : Optional Voltage regulator: AVR