

GENERATORS / AEDE 6001MK



The semi-silent eco diesel AEDE 6001MK generator is equipped with a centrifugal governor, single-phase alternator, THD (total harmonic distortion) value less than 6% and voltage accuracy between +2% and -2%. The starting capability is 2 times the rated current. Connection 220 V = N.2 SCHUKO sockets 16A 12 V DC = 2 screw type banana plugs one red (+) and one black (-) Protections Unipolar differential magneto-thermal switch. 10A fast fuse on the 12 V DC. Reading instrument Analogue voltmeter Regulations To connect to a compliant socket board

Handling

Rubber wheel and fold-away handlebar kit **Recommended use** Powerful electrical equipment, appliances and lighting that do not tolerate voltage variations between no load and full load and require a consistent voltage level.

Safe use

Before use, check the electrical requirements of the user and the maximum starting current of the loads.

GENERATOR	AEDE 6001MK
Maximum power (kVA/kW)	5/4
Continuous power (kVA/kW)	4.5/3.6
Voltage (Volts)	230
Frequency (Hz)	50
DC output power (V/A)	12/8.3
Fuel capacity (Litres)	12.5
Running time (h)	10
Noise level (dBA at 7m)	78
Battery	Yes
Wheel kit	Standard
Dry weight (Kg)	95
Dimensions (mm)	735x485x670
ENGINE	
Model	AMDE 186
Displacement (cc)	406
Power (Hp) at 3600 rpm	10
Туре	Diesel
Number of revolutions (rpm)	3000
Starting	Electric / Manual
Cooling	Air
Fuel	Diesel
ELECTRICAL COMPONENTS	
Type of pressure regulator	AVR
Protection rating	IP23
Unipolar residual-current device	Yes
Oil alarm device	Yes
Voltmeter	Yes
Fuel level warning light	Yes
ATS control panel	No

http://www.axo-group.com/en/products/generators/aede-6001mk.php

AXO GROUP SRL - Via Spallanzani, 15 - 42024 Castelnovo di Sotto (RE) Partita IVA, Codice Fiscale IT 02342860356 - Tel: 0522 688175 Fax: 0522 483731