












GENERATING SET GE 4554 KD



The images are for reference

FEATURES

- Automatic voltage regulator "AVR"
- Sockets: 1x230V 32A 2P+T CEE IP67 - 2x230V 16A 2P+T Schuko
- Isometer
- Circuit breaker
- Overload thermal shut off
- Protective frame
- Meets EC directives

Standard Equipment	 Diesel engine	 Air cooling	 Manual recoil	 Hours-meter							
	 Synchronous alternator	 Automatic voltage regulator	 Sockets	 Isometer	 Circuit breaker	 Thermal shut off	 Voltmeter				

- Options on request**
- Earthing kit
 - Trolley CTM 200
 - Hand trolley TRM 7554 (4 foldable handles)

Technical data GE 4554 KD

A.C. GENERATION - 50 Hz - Single-Phase synchronous alternator, self-excited, self-regulated, brushless

* Stand-by single-phase power	4.5 kVA (3.6 kW)/ 230 V / 19.6 A
* PRP single-phase power	4 kVA (3.2 kW)/ 230 V / 17.4 A
Cos φ	0.8
Insulation class	H

* Output powers according to ISO 8528-1

ENGINE - 4-stroke diesel, natural aspirated, direct injection, Air cooling

Model	KOHLER KD 350
* Stand-By net power	4.7 kW (6.3 HP)
* PRP net power	4.2 kW (5.7 HP)
Cylinders/ Displacement	1/ 349 cm ³
Speed	3000 rpm
Fuel consumption (75% of PRP)	1 l/h

* Powers according to ISO 3046-1

GENERAL SPECIFICATIONS

Tank capacity	4.3 l
Running time (75% of PRP)	4.3 h
IP protection degree	IP 54
*Dimensions LxIhx (mm)	910x525x613 mm
*Dry weight	107 kg
**Acoustic power LwA (pressure LpA)	99 dB(A) (74 dB(A) @ 7m)

*Dimensions and weight without trolley/trailer / **For fixed installation only in the EU market