

GENERATING SET

GE 7500 HBSL - HBSLE AVR

FEATURES

- Engine shut down for low oil level
- Electric starter (GE7500 HBSLE)
- Large fuel tank - 25l
- Combined system voltage regulation: electronic AVR + Compound
- Sockets: 1x400V 16A 3P+N+T CEE - 2x230V 16A 2P+T CEE
- ELCB-GFI (Ground Fault Interruptor) - Circuit breaker
- Silenced
- Meets EC Directives for safety and noise level



*Only HBSL
**Only HBSLE

The images are for reference

Standard Equipment											
	Petrol engine	Air cooling	Manual recoil*	Electric Starter**	Battery 12V**	Engine shut down (oil)	Hours-meter	Fuel level gauge			
	Synchronous alternator	AVR + COMPOUND (Auto. Voltage Regulator)	3~	1~	ELCB-GFI Circuit breaker	Voltmeter					

- Options on request**
- Earthing kit
 - Hand trolley CTM7/1 (4 wheels D 100 mm)
 - Hand trolley CTM7/3 (2 foldable handles and 2 wheels)
 - Hand trolley TRM7 (4 foldable handles)

- Versions on request**
- Schuko sockets

Technical data

GE7500 HBSL-AVR

GE7500 HBSLE-AVR

A.C. GENERATION - 50 Hz - *Three-phase synchronous alternator, self-excited, self-regulated, brushless*

***Stand-by three-phase power**

8 kVA (6.4 kW) / 400V /11.5A

***PRP three-phase power**

7 kVA (5.6 kW) / 400V /10.1A

***PRP single-phase power**

3 kVA / 230V /13A

Cos φ

0.8

Insulation class

H

* Output powers according to ISO 8528-1

ENGINE - 4-stroke petrol, OHV, Air cooling

Model

Honda GX 390

*** Stand-By net power**

8.2 kW (11.1 HP)

*** PRP net power**

6.4 kW (8.7 HP)

Cylinders/ Displacement

1/ 389 cm³

Speed

3000 rpm

Fuel consumption (75% of PRP)

2.4 l/h

* Powers according to SAE J1349

GENERAL SPECIFICATIONS

Tank capacity

25 l

Running time (75% of PRP)

10.4 h

IP protection degree

IP 23

*** Dimensions LxIxh**

750x520x660 mm

*** Dry weight**

93 Kg

104 Kg

**** Measured acoustic power LwA (pressure LpA)**

96 dB(A) (71 dB(A) @ 7m)

**** Guaranteed acoustic power LwA (pressure LpA)**

96 dB(A) (71 dB(A) @ 7m)

* Dimensions and weight without trolley/trailer / **Acoustic power according to European Directive 2000/14/EC

Mosa reserves the right to change this specification without notice. For further information please contact the sales department.