SERIE LC

LUX C10

LIGHTING TOWER



- VERTICAL TELESCOPIC MAST
  7 MT MAX EIGHT
- 4x150 W MULTI LED LAMPS
  2400 m² ILLUMINATED AREA
- OPTION TO CONNECT IN SERIES
  TO A SINGLE POWER SOURCE
- TWILIGHT SENSOR SUPPLIED
- GALVANIZED METALWORK
  80 µm POWDER COATING
- INLET PLUG: 16 A - 230 V
  OUTLET SOCKET: 16 A - 230 V
- 350° MAST ROTATION
  360° MANUAL FLOODLIGHTS
  TILTING

LUXTOWER

www.luxtower.com

LUX C10

TECHNICAL SHEET

ROUGH DIMENSIONS & WEIGHT

Dimensions min.	mm	1170 X 800 X 2350
Dimensions max.	mm	2030 X 1340 X 7000
Total weight without fuel	Kg	318

FEATURES

Rotation		350°
Floodlight	W	4 X 150
Lamps		LED
Outlet socket	A/V	16 - 230
Inlet Plug	A/V	16 - 230
Wind stability	Km/h	110
Options		Astronomic counter


5 LUX MIN.

ILLUMINATED AREA

- 5 m range
- 10 m range
- 20 m range
- 30 m range


2400 m²







UP TO LUX C10 CAN BE CONNECTED IN SEIRES TO AN EXTERNAL SOURCE SUCH AS MAIN ELECTRICITY OR GENERATOR*

*according with rated output and electric specs



3 LUX C10 CAN BE CONNECTED IN SERIES TO A TOWER WITH 8 KVA GENERATOR SET





33 units per truck



LUXTOWER

www.luxtower.com

Luxtower: Via Strada Nuova, 28 - 27050 Codevilla (PV) ITALY | TLF. +39 0383 365544 | Fax +39 0383 49702

LUXTOWER reserves the right to change any feature without prior notice. The illustrations may include optional equipment and/or accessories. Not contractual images. The technical indications described is this brochure correspond to the information availabble at the moment of printing. LUXTOWER® - 2016© All rights reserved.