MG 8000 BS/HA





Control Panel



Movable Base



Concealable Handles



We offer now what others will do tomorrow.



Genset s.p.a.

Via Stazione 5 - 27030 Villanova d'Ardenghi (PV) - Italy Phone:+39-0382-509 I

commerciale@genset.it www.genset.it



GenSet Next Gen technology for top business.

MG 8000 BS/HA / TECHNICAL DATA

SUPER SILENCED POWER GENERATOR OUTPUT POWER 6,2 KVA SINGLE-PHASE PETROL ENGINE 3000 RPM FUEL TANK 10,5 LT

Standard Features

- Low oil level cut out device
- 12 V built-in battery
- I x 230V I6A EEC single-phase socket
- I x 210V 32A EEC single-phase socket
- Power output protection
- Earth Leakage Circuit Breaker
- Voltmeter
- Hourmeter
- Fixed wheels and concealable handles for moving

Options available as factory options

- Versions with different voltages
- 60Hz version

Accessories on request

- AMF/ATS panel for auto start operation
- Remote control

Noise level

• Lwa 86 (61 dB at 7 mt)

AC generator - 50Hz

- Type: synchronous
- Single-phase power (stand-by): 6,2kVA 230V
- Single-phase power (prime): 5,6kVA 230V
- Power Factor: cos φ 0,8

Petrol Engine 3000 rpm

- Type: Honda GX390 1 cyl. 390 cm³
- Max power: II hp (8,2 kWm)
- Starting system: electric (12Vdc)
- · Cooling system: air
- Fuel consumption @ 75%: 3,3 lt/h

Other features

- Insulation Class: H
- Ambient temperature: 40 °C (*)
- Altitude: 1000 m (*)
- Mechanical Protection: IP 23
- Fuel tank capacity: 10,5 lt
- Dimensions (L x W x H): 941 x 614 x 720 mm
- Dry weight: 138 kg