



## LARIUS DALI K18945 POMPA AIRLESS A MEMBRANA

**Product price:** 

1.870,00 € tax excluded

## **Product description:**

LARIUS DALI K18945 AIRLESS PUMP WITH MEMBRANE

LARIUS DALI K18945 is an electric pump for airless painting to be used in high pressure without the aid of air (hence the term AIRLESS) capable of delivering a maximum flow rate of 4 l/m.

LARIUS DALI K18945 is a high-pressure electric pump equipped with an exclusive electric piloting system that allows the safeguard of the motor and of the board, in case of lack of grounding, sudden changes of tension, overheating and inadequate electric extensions.

The LARIUS DALI K18945 pump is driven by an electric motor (burst) coupled to an eccentric shaft. The shaft acts on the hydraulic piston which, by pumping oil from the hydraulic case, sends the suction membrane into fibrillation. The movement of the membrane creates a depression. The product is sucked in, pushed towards the outlet of the pump and sent through the hose to the guns

LARIUS DALI K18945 is able to apply in total efficiency in the aspiration and in the application of dense and viscous products, in addition thanks to the airless technology the drying times are considerably reduced, this allows the less contribution of diluting liquids to the product.

Thanks to LARIUS DALI K18945, the coating process will be faster and less costly; in fact, it makes it possible to cover the entire application zone in fewer passes.

All the components that characterize the LARIUS MIRÒ K18945 pump are of high quality and make it extremely resistant to wear and tear. This version of the LARIUS MIRÒ electropump includes a practical tank with a maximum capacity of 6 litres for the containment of the material to be nebulized, in this way the use will be even simpler and more immediate.

TECHNICAL FEATURES LARIUS DALI K18945





Max flow rate: 4 L/min Motor power: 1.1 Kw Max pressure: 250 bar Power supply: 230 VAC

Frequency: 50 Hz

Available voltages: 115 VAC (60 Hz) Available voltages: 400 VAC (50 Hz)

Guns: 1 AT 250 gun

Nozzle size: Up to 0. 025"

Minimum motogenerator power: 4.0 KW Single phase

Tank capacity: 50 I Length: 700 mm Width: 500 mm Height: 1000 mm Weight: 38 Kg.

Looking for an electric pump with different features? Here you can find the whole range of LARIUS or other specialized brands.

The images are purely indicative

## **Product features:**

Frequenza (Hz): 50 Tensione (V): 230

Portata massima (Lt/min): 4 Pressione (bar): 250 Max Capacità serbatoio (L): 50 Lunghezza (mm): 700 Larghezza (mm): 500 Altezza (mm): 770 Peso a secco (Kg): 38

Diametro massimo ugelli : 0.025"

Versione: Carrellata

Tipo di gruppo pompante: A membrana

